

The Suspended Water Heater Platform is engineered to support water heaters up to 20 U.S. gallons (up to 375 pounds total weight). This time and labor savings tool is designed for the Professional Contractor. Design features requested by plumbers are incorporated into a professional platform that can be suspended with all thread rod. See Installation Instructions for detail.

Product Information:

- Material: Pan: 14 gage CRS, galvanized Corner Brackets: 14 gage CRS, galvanized
- Wide platform allows water heaters up to 21-1/4" diameter
- Watertight corners and welded 1" steel drain body eliminate need for additional drain pan
- Static load rating 375 pounds with 2X safety factor (depending on structural anchorage)
- Galvanized steel construction
- Suspends with user supplied 3/8" or 1/2" threaded rod and hardware
- Four corner attachment points allows for seismic/sway bracing connection
- Patent pending

	Product Submittal
	Job Name:
	Date:
	Part Number: Qty:
THIS INFORMATION IS PROPRIETARY TO HOLDRITE AND IS SUBJECT	
TO CHANGE WITHOUT NOTICE. IT MAY NOT BE REPRODUCED IN	
PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION.	Architect / Owner:
HOIDRITF ®	
	Contractor:
	Notes:

CONVERTING MAKES JIFT METHODS INTO ENGINEERED SOLUTIONS?

800-321-0316 OR 760-744-6944 / FAX: 760-744-0507 / WWW.HOLDRITE.COM spec 40-SWHP-M RevE