

CABLE TIES

>> 554 SERIES

SPECIFICATION

Sioux Chief cable ties shall be used to organize or secure single or bundled CTS supply lines. Recommended for indoor use only.

Mounting cable tie shall be used to secure tube to walls, studs or other surfaces using #10 screw. Cable ties shall be compatible with copper, PEX or CPVC.

MATERIALS

Nylon 66, ultraviolet black (UVB), UL-94 V2 flame rating

MAXIMUM LOAD RATING

8" and 14½" models: 50 lbs.

21" and 36" models: 175 lbs.

SAFE WORKING TEMPERATURE

Maximum operating temperature: 185°F

Minimum operating temperatures: 32°F

Melting point: 400°F

DIMENSIONS

Model	8"	14½"	14-H	21"	36"
A: Width	⅜"	⅜"	⅝"	⅝"	⅝"
B: Maximum diameter	2"	4"	4"	6"	11"

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



554-08



554-608

Made in USA

Create Item Number

554-AB

e.g. **554-614**: 14½" mounting cable tie

MOUNTING A

_ = none

6 = includes mounting hole*

LENGTH B

08 = 8"

14 = 14½"

14H = 14" heavy duty

21 = 21"

36 = 36"

*Only available on 8" and 14½" models