

OUTLET BOX

▶▶ 696 SERIES

OxBox™

SPECIFICATION

Sioux Chief 696 Series OxBox single-hole outlet box shall be used where necessary in accessible plumbing applications. Box shall provide an appropriately sized hole for accessible line/fixture. Box shall incorporate mounting tabs, and channel for use with common, galvanized, flat brackets.

MATERIALS

ABS (white)

WORKING TEMPERATURE

Melting point: 200°F

Working temperature: 150°F


DIMENSIONS

A: Rough-in box inner width	4"				
B: Rough-in box overall depth	3½"				
C: Rough-in box inner height	5½"				
D: hole diameter	696-1	696-4	696-5	696-6	696-7
	0.85"	1.04"	1.3125"	1.915"	2.390"

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



696-4



Create Item Number

696-A

e.g. **696-4:** Outlet box with 1.04" diameter hole

HOLE SIZE A

- 1** = 0.85" hole
- 4** = 1.04" hole
- 5** = 1.3125" hole
- 6** = 1.915" hole (1½" Sch. 40 pipe)
- 7** = 2.390" hole (2" Sch. 40 pipe)

Accessories - Available Separately:

- 696-EX: Frame extension
- 696-1F: Frame only
- 696-LC: Louvered cover
- 696-SC: Solid cover
- 696-BC: Box clip
- 696-CF: Secondary drainage funnel
- 520-09: Support bracket