

ADJUSTABLE FLASHING DRAIN

» 833 SERIES

FinishLine™

SPECIFICATION

Sioux Chief 833 series FinishLine adjustable above-grade flashing drain shall be used where necessary in drainage systems. Flashing drain shall allow adjustment of 1-1/4" before the concrete pour, and 1-1/4" after the concrete pour. Flashing drain shall have an invertible flashing collar with openings to allow secondary drainage and a cast iron base adapter. Strainer shall be heel-resistant and meet applicable load requirements for intended use. Trap primer port shall be threaded 1/2" FIP for optional connection. Designed in accordance with ASME A112.6.3.

MATERIALS

Ring/strainer: Nickel-bronze, 304 Stainless steel
Head adapter/Coring sleeve/Clamping collar: gray ABS
Coring plug: high-impact polymer
Base adapter: cast iron

STRAINER LOAD RATING

	Large Top:	Std. Top
Nickel-Bronze:	750 lbs. (light duty)	1,650 lbs. (light duty)
Stainless Steel:	1,000 lbs. (light duty)	2,000 lbs. (light duty)

STRAINER FREE AREA


	Large Top:	Std. Top
Round:	13.4 in ²	8.5 in ²
Square:	16.4 in ²	12.75 in ²

DIMENSIONS

A: Connection size	2", 3", 4"
B: Ring/strainer diameter	
Round (Std. Large)	5-1/2" 6-1/2"
Square (Std. Large)	5-7/8" 7"
C: Flange diameter	8-1/2"
D: Base adapter height ¹	4"
E: Pre-pour adjustable height ¹	5" – 7"
F: Post-pour adjustable height	
Round Square	0" – 1-1/4" 5/16" – 1-1/4"

1 Max height noted with flashing collar inverted. Add 3/8" for Push-Joint connection

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



Create Item Number

833-ABCD

e.g. 833-625NQ: FinishLine 2" Push-Joint adjustable flashing drain with square nickel-bronze ring and strainer

CONNECTION TYPE A

2 = Cast iron No-Hub
6 = Cast iron Push-Joint

CONNECTION SIZE | TOP SIZE B

2 = 2" connection | Large top
25 = 2" connection | Std. top
3 = 3" connection | Large top
35 = 3" connection | Std. top
4 = 4" connection | Large top

RING/STRAINER TYPE C

NR = Round Nickel-bronze
SR = Round Stainless steel
NQ = Square Nickel-bronze
SQ = Square Stainless steel

OPTIONS D

V = Vandal-resistant strainer screws
H = Hinged Strainer²
E = 1-1/4" Extended strainer rim³
B = Complies with BABAA³
P = Push-Joint gasket for Sch. 40 pipe⁴

Accessories - Available Separately:

832-4HHD: Large Top hub drain finish fixture
832-3HHD: Std. Top hub drain finish fixture
832-4HPR: Large Top Finish Fixture with ABS ring/strainer
832-EX3: Iron extension adapter for Std. top⁵
832-EX4: Iron extension adapter for Large top⁵
832-P: Coring Plug wrench
832-S3: Leveling shim kit for Std. top
832-S4: Leveling shim kit for Large top
832-UM: Stainless mesh debris bucket for Large top
832-W: Flexible locating bristles kit
835-2: TrapShield™ for 2" drain outlet
835-3: TrapShield™ for 3" drain outlet
835-4: TrapShield™ for 4" drain outlet
863-FA: Round aluminum condensate funnel
863-FN: Round nik-brz condensate funnel
863-FNO: Oval nik-brz condensate funnel

2 Available for Large Top only | 3 Available for round nickel-bronze strainers only | 4 For 3" and 4" drains - In place of standard gasket | 5 Extends head 2" (min) to 4" (max) above Coring Sleeve