

CODE NUMBER

10021402

DESCRIPTION

SU-1009 Urinal and ROYAL 186 SMO Flushometer.

COMPONENTS

Flushometer: Code 3912694Urinal: Code 1101009

DETAILS

• Flush Volume: 0.25 gpf (0.9 Lpf)

• Nominal Dimensions: 14 $\frac{1}{4}$ " × 17 $\frac{1}{4}$ " × 25 $\frac{1}{2}$ " (362 × 438 × 648mm)

FLUSHOMETER FEATURES

- "User in View" Flashing LED
- No External Volume Adjustment to Ensure Water Conservation
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange w/Set Screw
- Stop Seat and Vacuum Breaker molded from PERMEX® Rubber Compound for Chloramine Resistance
- Four (4) Size C Batteries included
- Manual Override Flush Button
- "Low Battery" Flashing LED with Optional Audio Tone
- Optional 24-Hour Sentinel Flush
- 3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop with Vandal Resistant Stop Cap

FIXTURE FEATURES

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- · All mounting hardware included
- 100% factory flush tested



COMPLIANCES & CERTIFICATIONS























(ADA Compliant, BAA Compliant, BREEAM Water Credit, cUPC Green Certified, EPD, Green Globes Water Credit, HPD, LEED V4 Water Efficiency Credit, WaterSense Listed, Satisfies LEED Credits, WELL Building Standard)

DOWNLOADS

- Standard Spud Urinal Installation Instructions
- Optima SMO Installation Instructions
- Royal Exposed Installation Instructions
- SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and Maintenance Guide
- Additional Downloads

NOTES


All information contained within this document subject to change without notice.


WARRANTY

View Warranty Information



ROUGH-IN





Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com