


Class 150 (Standard)

FIG. 3124

Cap



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

FIGURE 3124 - CAP

Nominal Size	Dimension A	Approx. Wt. Each
In. (mm)	In. (mm)	Lbs. (kg)
1/8▲	0.53	0.03
6	13.46	0.01
1/4▲	0.63	0.05
8	16.00	0.02
3/8▲	0.74	0.07
10	18.80	0.03
1/2	0.87	0.11
15	22.10	0.05
3/4	0.97	0.18
20	24.64	0.08
1	1.16	0.30
25	29.46	0.14
1 1/4	1.28	0.44
32	32.51	0.20
1 1/2	1.33	0.55
40	33.78	0.25
2	1.45	0.85
50	36.83	0.39
2 1/2	1.70	1.49
65	43.18	0.68
3	1.80	2.20
80	45.72	1.00
3 1/2	1.90	3.02
90	48.26	1.37
4	2.08	3.79
100	52.83	1.72
6	2.55	8.77
150	64.77	3.98

▲ – Supplied in Steel only (Black and Galvanized).

MATERIAL SPECIFICATIONS

Dimensions: Fittings: ASME B16.3
Unions: ASME B16.39
Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Finish: Black or Hot Dip Galvanized per ASTM A153 Class A

Threads*: NPT per ASME B1.20.1

Pressure Ratings: Fittings: ASME B16.3
Unions: ASME B16.39
Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL/ULC Listed and FM Approved.

* British Standard threading per BS 21 available upon request.

PROJECT INFORMATION

APPROVAL STAMP

Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	