

CAREGIVER® FOLD-DOWN SEATS



Strong, sturdy and quality built, Mustee offers the most popular seat configurations and styles in both self-supporting and seats with legs.

Besides being a necessity for those who are unsteady on their feet and require assistance in the shower, many others enjoy Mustee premium fold-down shower seats for the convenience and comfort.


CareGiver® fold-down seats are the ideal solution for creating a comfortable and sturdy sit space in showers of all types.



Features


- Popular sizes and shapes
- Fire and mildew resistant
- When properly installed, wall-mount units can support up to 400 lbs., and leg-supported units can support up to 400 lbs.
- White cushion filled with high-resilience, high-density foam to maintain original shape
- Smooth cushion edges without corded piping – eliminates discomfort for pressure-sensitive bathers
- Rust-resistant stainless steel hardware
- Easy to install & clean – stain-resistant surface

Left-Hand Seat – Wall Mount




Size (A x B)	Model
26" x 21"	390.402
32" x 21"	390.404

Right-Hand Seat – Wall Mount




Size (A x B)	Model
26" x 21"	390.401
32" x 21"	390.403

Left-Hand Seat – With Legs




Size (A x B)	Model
26" x 21"	390.405
32" x 21"	390.406

Right-Hand Seat – With Legs




Size (A x B)	Model
26" x 21"	390.407
32" x 21"	390.408

Rectangular Seat – Wall Mount



Size (A x B)	Model
23" x 14 1/2"	390.413
26" x 14 1/2"	390.409
32" x 14 1/2"	390.410

Rectangular Seat – With Legs



Size (A x B)	Model
26" x 14 1/2"	390.411
32" x 14 1/2"	390.412

WALL MOUNTED UNITS:

General: Furnish and install as shown on plans, Fold-down Wall Mounted Shower Seat Model: _____, as provided by E. L. Mustee & Sons, Inc. Shower seat tubing shall be one-inch diameter, 18 gauge, type 304 stainless steel with #4 satin finish. Mounting brackets shall be 12-gauge type 304 stainless steel. Padded vinyl cushion shall have 1 1/2" high density, high-resilience foam, covered with fire and mildew resistant, UV inhibited, marine-grade Naugahyde. White cushion shall have no external piping. Shower seat unit shall comply with applicable building codes. Meets ANSI A117.1.

LEG SUPPORTED UNITS:

General: Furnish and install as shown on plans, Fold-down Leg-Supported Shower Seat Model: _____, as provided by E. L. Mustee & Sons, Inc. Shower seat tubing shall be one-inch diameter, 18 gauge, type 304 stainless steel with #4 satin finish. Shall include a fold-down mechanism with four support legs. Mounting brackets shall be 12-gauge type 304 stainless steel. Padded vinyl cushion shall have 1 1/2" high density, high-resilience foam, covered with fire and mildew resistant, UV inhibited, marine-grade Naugahyde. White cushion shall have no external piping. Shower seat unit shall comply with applicable building codes. Meets ANSI A117.1.