




One piece, single threshold model for recessed installation. Features 1" flange on three remaining sides. Center drain.



Model	A	B	C	D	E	WT.
3636F	36"	36"	18"	18"	18"	38
3642F	42"	36"	21"	21"	18"	45
4242F	42"	42"	21"	21"	21"	50
3448F	48"	34"	24"	24"	17"	44
3648F	48"	35 1/2"	24"	24"	15"	36
4248F	48"	42"	24"	24"	21"	47
4848F	48"	48"	24"	24"	24"	50
3460F	60"	34"	30"	30"	17"	50
3660F	60"	35 1/2"	30"	30"	17 3/4"	50
4260F	60"	41 1/2"	30"	30"	20 3/4"	60

#### Standards:

I.A.P.M.O. International Association of Plumbing and Mechanical Officials  
File No. 0687.

ANSI American National Standards Institute - Specifications Z-124.2.

HUD/FHA National Specifications UN-73.



## Florestone Molded Fiberglass Shower Receptors with THE EDGE

### Architect's Specifications

Furnish and install molded fiberglass one piece shower unit manufactured by Florestone Products Company. Unit to be manufactured of gel-coated fiberglass meeting Class C Flame Retardance and to be supplied with slip-resistant floor laminated for extra rigidity. Color will be white (unless otherwise specified). Unit to be supplied with a 2" PNC non-caulk drain.

Standard Color: White

Optional Colors

Color matching most major manufacturers' colors are available.

### Colors

Standard: White, Bone

Special: Granite (see pg. 12)

**Dimensions may vary  $\pm 1/4$ " inch.**

**Please check unit before installation.**

**Place receptor on a bed of mortar or plaster for warranty compliance.**

**Dimensions subject to  
change without notice.**

**Contact Florestone Products to  
verify product specifications.**



**FLORESTONE**  
*A Spec Above.™*

**FLORESTONE PRODUCTS CO., INC.**

2851 Falcon Drive • Madera, CA 93637

T. 559.661.4171 • T. 800.446.8827

F. 559.661.2070 • florestone.com