

DIELECTRIC FITTINGS**Forged Steel Dielectric Union**

200 CWP, 180°F max temp
NSF 372 (T-571NL)
ISO 9002
2-1/2", 3" & 4" are flanged



T-571NL
1/2" - 2"



T-571NL
2 1/2", 3" & 4"



Grommet

T-571M x SNL



Part No.	Size	Configuration	Model No.	Cs/Ct
301-103NL	1/2"	FNPT x Sweat	T-571NL	144/12
301-104NL	3/4"	FNPT x Sweat	T-571NL	144/12
301-123NL	3/4" x 1/2"	FNPT x Sweat	T-571NL	144/12
301-105NL	1"	FNPT x Sweat	T-571NL	120/12
301-125NL	1" x 3/4"	FNPT x Sweat	T-571NL	120/12
301-106NL	1-1/4"	FNPT x Sweat	T-571NL	48/6
301-107NL	1-1/2"	FNPT x Sweat	T-571NL	48/6
301-108NL	2"	FNPT x Sweat	T-571NL	24/6
301-119NL	2-1/2"	FNPT x Sweat	T-571NL	4/1
301-120NL	3"	FNPT x Sweat	T-571NL	3/1
301-121NL	4"	FNPT x Sweat	T-571NL	2/1
301-421	For 4" T-571NL		Grommet	- / -
301-203NL	1/2"	MNPT x Sweat	T-571M x SNL	144/12
301-204NL	3/4"	MNPT x Sweat	T-571M x SNL	144/12
301-205NL	3/4" x 1/2"	MNPT x Sweat	T-571M x SNL	144/12

Galvanized x Galvanized Dielectric Union

200 CWP, 180°F max temp
ISO 9002



T-572
FNPT x FNPT

301-303	1/2"	FNPT x FNPT	T-572	144/12
301-304	3/4"	FNPT x FNPT	T-572	120/12
301-305	1"	FNPT x FNPT	T-572	48/6
301-306	1-1/4"	FNPT x FNPT	T-572	48/6
301-307	1-1/2"	FNPT x FNPT	T-572	24/6
301-308	2"	FNPT x FNPT	T-572	20/2

Galvanized x Brass Dielectric Union

200 CWP, 180°F max temp
NSF 372
ISO 9002



T-573NL
FNPT x FNPT

301-323NL	1/2"	FNPT x FNPT	T-573NL	144/12
301-324NL	3/4"	FNPT x FNPT	T-573NL	120/12
301-325NL	1"	FNPT x FNPT	T-573NL	48/6

Black Gas Service Dielectric Union

200 CWP, 180°F max temp
ISO 9002



T-574
FNPT x FNPT

301-333	1/2"	FNPT x FNPT	T-574	144/12
301-334	3/4"	FNPT x FNPT	T-574	120/12
301-335	1"	FNPT x FNPT	T-574	48/6
301-336	1-1/4"	FNPT x FNPT	T-574	48/6
301-337	1-1/2"	FNPT x FNPT	T-574	24/6
301-338	2"	FNPT x FNPT	T-574	20/2