



MALLEABLE FITTINGS

We offer one of the most extensive selections of black and galvanized malleable iron fittings in the industry. Available in 13 diameters from 1/8" to 6", every fitting is produced to exact specifications. All galvanized products are zinc-coated for water applications and meet all low-lead requirements. In addition, all of our iron fittings undergo our rigorous testing and quality inspections.

1/8" • SCHEDULE 40 WELDED STEEL NIPPLES



LENGTH	BULK PART NBR				BARCODED PART NBR			
	BLACK	GALV	INNER QTY	MC QTY	BLACK	GALV	INNER QTY	MC QTY
Close	580-001	560-001	25	100	580-001HC	560-001HC	10	480
1-1/2	580-015	560-015	25	100	580-015HC	560-015HC	10	480
2	580-020	560-020	25	100	580-020HC	560-020HC	10	480
2-1/2	580-025	560-025	25	100	580-025HC	560-025HC	10	480
3	580-030	560-030	25	100	580-030HC	560-030HC	10	480
3-1/2	580-035	560-035	25	100	580-035HC	560-035HC	10	240
4	580-040	560-040	25	100	580-040HC	560-040HC	10	240
4-1/2	580-045	560-045	25	100	580-045HC	560-045HC	10	240
5	580-050	560-050	25	100	580-050HC	560-050HC	10	240
5-1/2	580-055	560-055	25	100	580-055HC	560-055HC	10	240
6	580-060	560-060	25	100	580-060HC	560-060HC	10	240
7	580-070	560-070	25	100	-	-	-	-
8	580-080	560-080	-	25	580-080HC	560-080HC	25	150
9	580-090	560-090	25	100	-	-	-	-
10	580-100	560-100	-	25	580-100HC	560-100HC	25	150
11	580-110	560-110	25	100	-	-	-	-
12	580-120	560-120	-	25	580-120HC	560-120HC	25	150

1/4" • SCHEDULE 40 WELDED STEEL NIPPLES



LENGTH	BULK PART NBR				BARCODED PART NBR			
	BLACK	GALV	INNER QTY	MC QTY	BLACK	GALV	INNER QTY	MC QTY
Close	581-001	561-001	25	100	581-001HN	561-001HN	-	10
1-1/2	581-015	561-015	25	100	581-015HC	561-015HN	10	-
2	581-020	561-020	25	100	581-020HN	561-020HN	-	10
2-1/2	581-025	561-025	25	100	581-025HC	561-025HC	10	480
3	581-030	561-030	25	100	581-030HN	561-030HN	-	10
3-1/2	581-035	561-035	25	100	581-035HC	561-035HC	10	240
4	581-040	561-040	25	100	581-040HN	561-040HN	-	10
4-1/2	581-045	561-045	25	100	581-045HC	561-045HC	10	240
5	581-050	561-050	25	100	581-050HN	561-050HN	-	10
5-1/2	581-055	561-055	25	100	581-055HC	561-055HC	10	240