



SECTION 02 **BLACK &** **GALVANIZED NIPPLES**

This section lists out our extensive offering for steel nipples and pipe. Each section conveniently lays out the different offerings of each type of nipple in black, galvanized, wholesale and retail.

For Steel Pipe, Pre-Cut Pipe, Extra-Heavy Nipples, Seamless Nipples, please visit our wholesale literature page at our website: www.bkproducts.com

Black & Galv. Nipples0018

- Schedule 40
- Schedule 80
- Schedule 80 Seamless
- Schedule 160 Seamless

Nipple Assortments031

- Series 6700

Schedule 40 Precut Pipe033



SCHED. 40 NIPPLES | BLACK & GALVANIZED



1/8in Diameter Schedule 40 Nipples

MIP x MIP

BULK PART NUMBER

Length	Black	Galvanized	Inner	MC
Close	580-001	560-001	25	100
1-1/2in	580-015	560-015	25	100
2in	580-020	560-020	25	100
2-1/2in	580-025	560-025	25	100
3in	580-030	560-030	25	100
3-1/2in	580-035	560-035	25	100
4in	580-040	560-040	25	100
4-1/2in	580-045	560-045	25	100
5in	580-050	560-050	25	100
5-1/2in	580-055	560-055	25	100
6in	580-060	560-060	25	100
7in	580-070	560-070	100	-
8in	580-080	560-080	100	-
9in	580-090	560-090	100	-
10in	580-100	560-100	100	-
11in	580-110	560-110	100	-
12in	580-120	560-120	100	-

BARCODED PART NUMBER

Length	Black	Galvanized	Inner	MC
Close	580-001HC	560-001HC	10	480
1-1/2in	580-015HC	560-015HC	10	480
2in	580-020HC	560-020HC	10	480
2-1/2in	580-025HC	560-025HC	10	480
3in	580-030HC	560-030HC	10	480
3-1/2in	580-035HC	560-035HC	10	240
4in	580-040HC	560-040HC	10	240
4-1/2in	580-045HC	560-045HC	10	240
5in	580-050HC	560-050HC	10	240
5-1/2in	580-055HC	560-055HC	10	240
6in	580-060HC	560-060HC	10	240
7in	-	-	-	-
8in	580-080HC	560-080HC	25	150
9in	-	-	-	-
10in	580-100HC	560-100HC	25	150
11in	-	-	-	-
12in	580-120HC	560-120HC	25	150

1/4in Diameter Schedule 40 Nipples

MIP x MIP

BULK PART NUMBER

Length	Black	Galvanized	Inner	MC
Close	581-001	561-001	25	100
1-1/2in	581-015	561-015	25	100
2in	581-020	561-020	25	100
2-1/2in	581-025	561-025	25	100
3in	581-030	561-030	25	100
3-1/2in	581-035	561-035	25	100
4in	581-040	561-040	25	100
4-1/2in	581-045	561-045	25	100
5in	581-050	561-050	25	100
5-1/2in	581-055	561-055	25	100
6in	581-060	561-060	25	100
7in	581-070	561-070	100	-
8in	581-080	561-080	100	-
9in	581-090	561-090	100	-
10in	581-100	561-100	100	-
11in	581-110	561-110	100	-
12in	581-120	561-120	100	-

BARCODED PART NUMBER

Length	Black	Galvanized	Inner	MC
Close	581-001HC	561-001HC	10	480
1-1/2in	581-015HC	561-015HC	10	480
2in	581-020HC	561-020HC	10	480
2-1/2in	581-025HC	561-025HC	10	480
3in	581-030HC	561-030HC	10	480
3-1/2in	581-035HC	561-035HC	10	240
4in	581-040HC	561-040HC	10	240
4-1/2in	581-045HC	561-045HC	10	240
5in	581-050HC	561-050HC	10	240
5-1/2in	581-055HC	561-055HC	10	240
6in	581-060HC	561-060HC	10	240
7in	-	-	-	-
8in	581-080HC	561-080HC	25	150
9in	-	-	-	-
10in	581-100HC	561-100HC	25	150
11in	-	-	-	-
12in	581-120HC	561-120HC	25	150



1/8-in Diameter Nipples
Schedule 40
Red Brass

Item No.	Size	Inner	MC
460-001	1/8in x Close	5	25
460-015	1/8in x 1-1/2in	5	25
460-020	1/8in x 2in	5	25
460-025	1/8in x 2-1/2in	5	25
460-030	1/8in x 3in	5	25
460-035	1/8in x 3-1/2in	5	25
460-040	1/8in x 4in	5	25
460-050	1/8in x 5in	5	25
460-060	1/8inx 6in	5	25



3/8-in Diameter Nipples
Schedule 40
Red Brass

Item No.	Size	Inner	MC
462-001	3/8in x Close	5	25
462-015	3/8in x 1-1/2in	5	25
462-020	3/8in x 2in	5	25
462-025	3/8in x 2-1/2in	5	25
462-030	3/8in x 3in	5	25
462-035	3/8in x 3-1/2in	5	25
462-040	3/8in x 4in	5	25
462-045	3/8in x 4-1/2in	5	25
462-050	3/8in x 5in	5	25
462-055	3/8in x 5-1/2in	5	25
462-060	3/8in x 6in	5	25
462-080	3/8in x 8in	5	25



1/4-in Diameter Nipples
Schedule 40
Red Brass

Item No.	Size	Inner	MC
461-001	1/4in x Close	5	25
461-015	1/4in x 1-1/2in	5	25
461-020	1/4in x 2in	5	25
461-025	1/4in x 2-1/2in	5	25
461-030	1/4in x 3in	5	25
461-035	1/4in x 3-1/2in	5	25
461-040	1/4in x 4in	5	25
461-045	1/4in x 4-1/2in	5	25
461-050	1/4in x 5in	5	25
461-055	1/4in x 5-1/2in	5	25
461-060	1/4in x 6in	5	25



1/2-in Diameter Nipples
Schedule 40
Red Brass

Item No.	Size	Inner	MC
463-001	1/2in x Close	5	25
463-015	1/2in x 1-1/2in	5	25
463-020	1/2in x 2in	5	25
463-025	1/2in x 2-1/2in	5	25
463-030	1/2in x 3in	5	25
463-035	1/2in x 3-1/2in	5	25
463-040	1/2in x 4in	5	25
463-045	1/2in x 4-1/2in	5	25
463-050	1/2in x 5in	5	25
463-055	1/2in x 5-1/2in	5	25
463-060	1/2in x 6in	5	25
463-080	1/2in x 8in	5	25
463-100	1/2in x 10in	5	25
463-120	1/2in x 12in	5	10





FINISHES

Black, Galvanized and Their Designed Applications

Our fittings, nipples and pipes are offered in three finishes: Black, Galvanized and Red Brass. Each finish offers unique application advantages over each other making them ideal for particular projects.

BLACK FINISH

Accessories with black finish are generally used for lubricant oil, grease, LP gas, natural gas, gases (nitrogen, oxygen, etc.), steam and diesel. This finish is best suited for normal use where an inner rustproof protection is not required.


GALVANIZED FINISH

Our Galvanized Finish offering is used for hot and cold water systems, refrigeration, sprinklers, compressed air, gasoline, diesel, alcohol, and some other applications where conducted fluid needs inner rustproof protection.


These fittings are manufactured by hot-dip galvanizing according to ASTM A-153. There are several ways to protect iron against rust, but none better than our hot-dip galvanizing process. Hot-dip galvanizing is one of the most efficient, practical and economical ways to protect iron and steel as zinc resists very well environment, air, and water corrosion for long lasting protection.

Galvanizing protects from corrosion the following ways:

- 1) It offers a long lasting isolating coverage made of metallic zinc and zinc alloy expertly applied to our iron.
- 2) Since zinc is bonded to iron as part of the iron-zinc combination, the protection works at a molecular level throughout the union. This serves as both a mechanical and corrosion protector.




Zinc resists the environment's corrosive actions. Opposite to this, most of the organic coatings (paintings) are environmentally unstable and need to be renewed frequently. When a little failure occurs, corrosion starts and it begins to become larger under the protective coating.



Cathodic iron protection, provided by the metallic zinc coating, is factually based on corrosion being an electro-chemical process.

As zinc is a highly active electrochemical element, it tends to absorb oxygen before iron does it. Furthermore, this condition



creates additional protection against zinc hydroxide. This cathodic protection prevents corrosion to exposed parts, due to any discontinuity or mechanical damage on the coating.



NIPPLE PRODUCTS

We manufacture threaded and flat end nipples with galvanized and black finishes alongside aluminum and brass options. Processed diameters range from 1/8-in to 6-in and lengths from close thread to 12-in for nipples with pipe lengths from 10 ft to 21-ft.

WELDED STEEL NIPPLE PRODUCTS

Offering includes:

- Schedule 40 Nipple, Black and Galvanized
- Schedule 80 Nipple, Black and Galvanized
- Galvanized Conduit Nipple (UL listed)

Normal applications for threaded product lines are steam, gas, water and compressed air. Schedule should be selected based on the conduction lines required pressure. Our galvanized conduit is best with metallic pipes used for installation of wires and cables.

Our welded steel nipples are manufactured to ASTM A733 and ASME B1.20.1 specifications. UL6 specification applies for galvanized conduit nipples.

SEAMLESS STEEL NIPPLE PRODUCTS

This nipple offering is manufactured with seamless steel pipe that complies with ASTM A106, Grade B standard.

- Schedule 40 Nipple, Black and Electro-galvanized (includes yellow-zinc finish)
- Schedule 80 Nipple, Black and Electro-galvanized (includes yellow-zinc finish)
- Schedule 160 Nipple, Black and Electro-galvanized (includes yellow-zinc finish)

These seamless nipples are ideal for high temperature service applications. Schedule should be selected based on the conduction lines required pressure.

Our seamless steel nipples are manufactured according to ASTM A733 and ASME B1.20.1 standards.

BRASS NIPPLES

Southland brass nipples are manufactured with ASTM B43 compliant brass tube.

Brass nipple applications include plumbing, heater lines, boilers and related purposes.

These are manufactured according to ASTM B687 and ASME B1.20.1 standards.



NIPPLE SPECIFICATIONS

Material, Mechanical & Chemical Properties

Southland nipples are manufactured to the exacting technical specs noted below. All nipple products undergo rigorous testing to help ensure guaranteed quality throughout all product groups.

MATERIAL SPECIFICATIONS

Our line of steel nipples and ready cut pipe is manufactured according to the strictest worldwide specifications. For this reason its response to corrosion, temperature and working pressures will be excellent, promoting long lasting and reliable fluid conduction systems.

MECHANICALS PROPERTIES

Welded steel pipe nipples and ready-cut pipe, schedule 40 & 80, ERW type (Electric Resistance Welded), Grade A are manufactured to the ASTM A-53 standard.

Seamless steel pipe nipples and ready-cut pipe, schedule 40, 80, 160 & XXS, Grade B are manufactured to the ASTM A-106 standard.

	GRADE A	GRADE B
Tensile strength	48,000 psi	60,000 psi
Yield strength	30,000 psi	35,000 psi
Elongation in 2 inches	$E = \frac{625000 \cdot A \cdot 0.2}{U \cdot 0.9}$	$E = \frac{625000 \cdot A \cdot 0.2}{U \cdot 0.9}$

CHEMICAL PROPERTIES

Chemical composition (%) – maximum values

	CARBON	COOPER A	NICKEL A	CHROME A	MOLYBDENUM A	VANADIUM A	MANGANESE	PHOSPHORUS	SULFUR
Grade A: A53	0.25%	0.4%	0.4%	0.4%	0.15%	0.08%	0.95%	0.05%	0.045%
Grade B: A106	0.30%	0.4%	0.4%	0.4%	0.15%	0.08%	0.29-1.06%	0.035%	0.035%

A – The combination of these 5 elements should not exceed 1.00%



PRESSURES

Maximum allowable working pressure - Grade A welded carbon steel pipe threaded nipples.

Size	Depth Thread	OD	Wall Thickness	Schedule	-20°-100°F (PSI)	200°F (PSI)	300°F (PSI)	400°F (PSI)	500°F (PSI)	600°F (PSI)	650°F (PSI)
1/8-in	0.027	0.405	0.068	40	2948	2948	2948	2948	2948	2782	2702
	0.027	0.405	0.095	80	5222	5222	5222	5222	5222	4857	4756
1/4-in	0.046	0.540	0.088	40	2229	2229	2229	2229	2229	2084	2038
	0.046	0.540	0.119	80	4085	4085	4085	4085	4085	3823	3729
3/8-in	0.046	0.675	0.091	40	1897	1897	1897	1897	1897	1777	1739
	0.046	0.675	0.126	80	3547	3547	3547	3547	3547	3281	3229
1/2-in	0.054	0.840	0.109	40	1879	1879	1879	1879	1879	1747	1715
	0.054	0.840	0.147	80	3301	3301	3301	3301	3301	3067	3006
3/4-in	0.054	1.050	0.113	40	1601	1601	1601	1601	1601	1493	1454
	0.054	1.050	0.154	80	2795	2795	2795	2795	2795	2605	2555
1-in	0.066	1.315	0.133	40	1438	1438	1438	1438	1438	1335	1315
	0.066	1.315	0.179	80	2505	2505	2505	2505	2505	2320	2281
1-1/4-in	0.066	1.660	0.140	40	1254	1254	1254	1254	1254	1169	1145
	0.066	1.660	0.191	80	2172	2172	2172	2172	2172	2021	1980
1-1/2-in	0.066	1.900	0.145	40	1162	1162	1162	1162	1162	1086	1064
	0.066	1.900	0.200	80	2028	2028	2028	2028	2028	1883	1846
2-in	0.066	2.375	0.154	40	1034	1034	1034	1034	1034	964	940
	0.066	2.375	0.218	80	1834	1834	1834	1834	1834	1699	1660
2-1/2-in	0.096	2.875	0.203	40	1037	1037	1037	1037	1037	964	945
	0.096	2.875	0.276	80	1785	1785	1785	1785	1785	1657	1621
3-in	0.096	3.500	0.216	40	953	953	953	953	953	886	866
	0.096	3.500	0.300	80	1657	1657	1657	1657	1657	1537	1507
4-in	0.096	4.500	0.237	40	872	872	872	872	872	809	792
	0.096	4.500	0.337	80	1518	1518	1518	1518	1518	1408	1379
6-in	0.096	6.625	0.280	40	771	771	771	771	771	713	700
	0.096	6.625	0.432	80	1434	1434	1434	1434	1434	1328	1301

