

COPPER FITTINGS FOR PLUMBING AND MECHANICAL APPLICATIONS

Job Name	Contractor
Job Location	Wholesaler
Engineer	Streamline® Rep

Product Description:

Streamline® Wrot Copper Pressure and DWV fittings for use in plumbing or mechanical applications. Available sizes ranging from 1/4" to 8" in diameter. Product is designed to join ASTM B88 and ASTM B280 Seamless Copper Tube.

Material:

Streamline® Wrot Copper fittings shall be made from material in compliance with UNS C12200 grade of copper.

Key Specifications:

Streamline® Wrot Copper, solder joint, pressure fittings shall conform to the NSF/ANSI 61 Annex G requirements. Wrot copper pressure fittings shall be manufactured to meet ASME B16.22 and MSS SP104. Wrot DWV copper fittings shall be made to meet ASME B16.29. All threaded fittings conform to ASME B1.20.1.

Installation:

Installations shall comply with the latest applicable building codes for the local jurisdiction. For detailed installation instructions, consult the Copper Development Association at copper.org.

References:

NSF/ANSI 61 Annex G	Safe Drinking Water Act (third party certification)
C12200	99.9% pure copper
ASME B16.22	Wrot Copper and Copper Alloy Solder Joint Pressure Fittings
MSS SP104	Wrot Copper Solder and Joint Pressure Fittings
ASME B16.29 ASME	Drain, Waste and Vent (DWV) Fittings
B1.20.1	Threaded Fittings

Other Applicable Standards:

ASTM B88	Seamless Copper Water and Gas Tube (Types K, L, M)
ASTM B280	Seamless Copper Tube for Air Conditioning and Refrigeration

Copper [tube or fitting] UNS C122000 has been evaluated by NSF International to NSF/ANSI 61 for use in drinking water supplies of pH 6.5 and above. Drinking water supplies that are less than pH 6.5 may require corrosion control to limit leaching of copper into the drinking water.

90° ELBOW (CONT.)

LONG RADIUS WE-506L

FTG x FTG



Part	Size	Box	Ctn	Wt
W 02650	1-1/4	5	50	0.44
W 02655	1-1/2	5	50	0.63
W 02659	2	1	10	1.23

FITTING REDUCER

WC-403

FTG x C



Part	Size	Box	Ctn	Wt
W 01306	1/4 x 1/8	50	2000	0.01
W 01312	3/8 x 1/4	50	2000	0.02
W 01314	x 1/8	50	2800	0.01
W 01315	1/2 x 3/8	50	750	0.03
W 01317	x 1/4	50	1700	0.02
W 01320	5/8 x 1/2	100	1000	0.04
W 01321	x 3/8	100	900	0.04
W 01322	x 1/4	100	900	0.04
W 01325	3/4 x 5/8	50	500	0.06
WB01326	x 1/2	25	500	0.06
W 01327	x 3/8	50	500	0.06
W 01337	1 x 3/4	25	250	0.11
W 01338	x 5/8	25	250	0.10
W 01339	x 1/2	25	250	0.10
W 01340	x 3/8	20	200	0.10
W 01343	1-1/4 x 1	10	100	0.17
W 01345	x 3/4	10	100	0.17
W 01347	x 1/2	10	100	0.16
W 01350	1-1/2 x 1-1/4	10	100	0.23
W 01351	x 1	10	100	0.24
W 01353	x 3/4	10	100	0.23
W 01355	x 1/2	10	100	0.22
W 01358	2 x 1-1/2	-	100	0.44
W 01359	x 1-1/4	-	100	0.43
W 01360	x 1	-	100	0.45
W 01362	x 3/4	-	100	0.43
W 01364	x 1/2	-	100	0.42
W 01367	2-1/2 x 2	-	50	0.62
W 01368	x 1-1/2	-	50	0.57
W 01369	x 1-1/4	-	50	0.62
W 01370	x 1	-	50	0.63
W 01376	3 x 2-1/2	-	25	1.00
W 01377	x 2	-	25	0.89
W 01378	x 1-1/2	-	50	0.92
W 01379	x 1-1/4	-	50	1.01
W 01381	3-1/2 x 3	-	20	1.28
W 01382	x 2-1/2	-	20	1.37
W 01383	x 2	-	20	1.47
W 01386	4 x 3-1/2	-	20	1.74
W 01387	x 3	-	15	1.77
W 01388	x 2-1/2	-	15	1.83
W 01389	x 2	-	15	1.86
W 01390	5 x 4	-	1	3.24
W 01391	x 3	-	1	2.76
W 01393	x 2	-	1	2.66
W 01394	6 x 5	-	1	4.80
W 01395	x 4	-	1	4.32
W 01396	x 3	-	1	4.49

HANGER

HI-EAR W-124

C



Part	Size	Box	Ctn	Wt
A 03167	1/2	100	1000	0.03
A 03168	3/4	25	500	0.04
A 03171	1	25	250	0.04

PLUG

FITTING

WC-416

(SIZES 1/8 THRU 11/2
BRASS ROD)

FTG



Part	Size	Box	Ctn	Wt
A 01402	1/8	50	500	0.01
A 01422	1/4	100	4000	0.01
A 01392	3/8	50	2000	0.02
A 01504	1/2	50	1200	0.03
A 01529	3/4	50	600	0.07
A 01556	1	25	375	0.12
A 01590	1-1/4	15	180	0.20
A 01628	1-1/2	10	120	0.28

RETURN BEND

WE-512

C x C



Part	Size	Box	Ctn	Wt
W 06025	1/4 x 4-1/2	25	150	0.10
W 06020	x 1-1/2	25	850	0.02
W 06048	3/8 x 6	-	100	0.21
W 06045	x 4	-	200	0.14
W 06041	x 3	25	250	0.11
W 06036	x 2	50	300	0.06
W 06035	x 1-29/32	50	300	0.08
W 06032	x 1-1/2	50	500	0.06
W 06069	1/2 x 6	5	30	0.30
W 06062	x 3-3/8	10	100	0.18
W 06060	x 3	25	150	0.16
W 06058	x 2-1/2	25	250	0.14
W 06056	x 2-1/4	25	250	0.13
W 06053	x 1-7/8	25	250	0.11
W 06051	x 1-9/16	25	250	0.10
W 06084	5/8 x 4	-	120	0.25
W 06081	x 3-3/8	10	90	0.24
W 06077	x 2-1/2	10	100	0.17
W 06074	x 2-1/8	10	100	0.16
W 06073	x 2	10	100	0.15
W 06099	3/4 x 12	-	15	0.88
W 06095	x 3-3/8	10	100	0.29
W 06092	x 2-1/2	10	100	0.23
W 60111	1 x 3-1/4	5	50	0.49
W 60110	x 3	5	50	0.47
W 60121	1-1/4 x 3-3/4	5	50	0.65
W 60131	1-1/2 x 4-1/2	5	25	1.00
W 60140	2 x 5-1/2	5	25	1.92

P-TRAP

SUCTION LINE WE-554P

C x C



Part	Size	Box	Ctn	Wt
W 60999	1/2	10	50	0.38
W 61008	5/8	10	50	0.51
W 61000	3/4	5	25	0.63
W 61001	1	3	15	0.87
W 61002	1-1/4	4	20	1.16
W 61003	1-1/2	4	4	2.28
W 61009	2	-	3	3.87

TEE

WT-600

C x C x C



Part	Size	Box	Ctn	Wt
W 40306	1/8	100	2400	0.01
W 04000	1/4	50	1700	0.02
W 04001	3/8	50	500	0.04
WB04006	1/2	50	500	0.07
W 04017	5/8	25	250	0.12
WB04031	3/4	25	200	0.16
WB04048	1	10	100	0.29
W 04068	1-1/4	5	50	0.42
W 04084	1-1/2	5	50	0.60
W 40102	2	5	25	1.14
W 40123	2-1/2	2	20	1.72
W 40152	3	2	10	2.77
W 40190	3-1/2	1	5	5.66
W 40200	4	1	5	5.99
W 40400	5	-	1	12.38
W 40500	6	-	1	20.85
W 40525	8	-	1	36.81

REDUCING

W 40368	1/8 x 1/8 x 1/4	50	750	0.03
W 04016	1/4 x 1/4 x 1/2	50	500	0.08
W 04005	x 3/8	50	500	0.04
W 40324	x 1/8	50	1700	0.02
W 40330	x 1/8 x 1/4	50	500	0.02
W 40332	x 1/8	50	1700	0.02
W 04015	3/8 x 3/8 x 1/2	50	500	0.09
W 04002	x 1/4	50	500	0.04
W 40350	x 1/8	50	500	0.04
W 04003	x 1/4 x 3/8	50	500	0.05
W 40004	x 1/4	50	500	0.04
W 40358	x 1/8	50	750	0.04
W 40363	x 1/8 x 3/8	50	750	0.05
W 40364	x 1/4	50	750	0.04
W 40366	x 1/8	50	450	0.05
W 40467	1/2 x 1/2 x 1	10	100	0.35
W 04047	x 3/4	25	250	0.11

TEE (CONT.)

REDUCING

W 04029	x 5/8	25	250	0.10
W 04007	x 3/8	50	500	0.08
W 04008	x 1/4	50	500	0.06
W 04014	x 1/8	50	500	0.08
W 04009	x 3/8 x 1/2	50	500	0.09
W 04010	x 3/8	50	500	0.08
W 04011	x 1/4	50	500	0.08
W 04012	x 1/4 x 1/2	50	500	0.09
W 040367	x 3/8	50	500	0.08
W 04013	x 1/4	50	500	0.09
W 04046	5/8 x 5/8 x 3/4	25	250	0.15
W 04018	x 1/2	25	250	0.10
W 04019	x 3/8	25	250	0.10
W 04020	x 1/4	25	250	0.10
W 04021	x 1/2 x 5/8	25	225	0.13
W 04022	x 1/2	25	250	0.11
W 04023	x 3/8	25	225	0.11
W 04025	x 3/8 x 5/8	25	250	0.15
W 04026	x 1/2	25	225	0.14
W 04027	x 3/8	25	250	0.11
W 04065	3/4 x 3/4 x 1	10	100	0.22
W 04032	x 5/8	25	250	0.17
WB04033	x 1/2	25	250	0.12
W 04034	x 3/8	25	250	0.11
W 04035	x 1/4	25	250	0.11
W 04036	x 5/8 x 3/4	25	250	0.19
W 04037	x 5/8	25	250	0.17
WB04041	x 1/2 x 3/4	25	250	0.16
W 04042	x 5/8	25	150	0.17
WB04043	x 1/2	25	250	0.13
W 04044	x 3/8	25	250	0.12
W 04045	x 1/4	25	225	0.15
W 40230	x 3/8 x 3/4	25	250	0.19
W 40231	x 1/2	25	250	0.17
W 40232	x 3/8	25	250	0.12
W 40101	1 x 1 x 1-1/2	5	50	0.47
W 04082	x 1-1/4	5	50	0.31
WB04049	x 3/4	10	100	0.24
W 04050	x 5/8	10	100	0.27
WB04051	x 1/2	10	100	0.21
W 04052	x 3/8	10	100	0.19
W 04055	1x3/4x1	10	100	0.30
W 04056	x 3/4	10	100	0.25
W 04057	x 5/8	10	90	0.43
W 04058	x 1/2	10	100	0.23
W 04059	x 3/8	10	100	0.21
W 40233	x 5/8 x 1	10	100	0.33
W 40234	x 3/4	10	90	0.30
W 40235	x 5/8	10	100	0.31
W 40236	x 1/2	10	90	0.35
W 04061	x 1/2 x 1	10	100	0.30
W 04062	x 3/4	10	100	0.28
W 04063	x 1/2	10	100	0.21
W 40122	1-1/4x1-1/4 x2	2	20	0.89
W 40100	x 1-1/2	5	50	0.49
W 04069	x 1	5	50	0.41
W 04070	x 3/4	5	50	0.35
W 04071	x 1/2	5	50	0.32
W 04072	x 3/8	5	50	0.29
W 04073	x 1 x 1-1/4	5	50	0.48
W 04074	x 1	5	50	0.46
W 04075	x 3/4	5	50	0.38
W 04076	x 1/2	5	50	0.36
W 04078	x 3/4 x 1-1/4	5	50	0.45
W 04079	x 1	5	50	0.46
W 04080	x 3/4	5	50	0.37
W 04081	x 1/2	5	50	0.34
W 04083	1/2 x 1-1/4	5	50	0.57
W 40121	1-1/2x1-1/2x2	2	20	1.21
W 04085	x 1-1/4	5	50	0.57
W 04086	x 1	5	50	0.52
W 04087	x 3/4	5	50	0.47
W 04088	x 1/2	5	50	0.42
W 04089	x 3/8	5	50	0.41
W 04090	x1-1/4x1-1/2	5	50	0.68
W 04091	x 1-1/4	5	50	0.69
W 04092	x 1	5	50	0.57
W 04093	x 3/4	5	50	0.57
W 04094	x 1/2	5	50	0.45
W 04095	x 1 x 1-1/2	5	50	0.68
W 04096	x 1-1/4	5	50	0.65
W 04097	x 1	5	50	0.61
W 04098	x 3/4	5	50	0.56
W 40237	x 1/2	5	30	0.45
W 04099	x 3/4 x 1-1/2	5	50	0.67
W 40239	x 1-1/4	5	50	0.75
W 40240	x 1	5	50	0.55

COPPER FITTING DATA

TEMPERATURE - PRESSURE RATINGS OF SOLDER JOINTS					
ALLOYS USED FOR JOINTS	SERVICE TEMPERATURE °F	STANDARD TUBE SIZE, TYPES K, L, AND M			
		WATER AND NON-CORROSIVE LIQUIDS & GASES			
		1/4 to 1	1-1/4 to 2	2-1/2 to 4	5 to 8
50 / 50 Tin Lead Solder Not to be used in potable water systems	100	200	175	150	135
	150	150	125	100	90
	200	100	90	75	70
	250	85	75	50	45
95 / 5 Tin-Antimony Solder	100	1090	850	705	660
	150	625	485	405	375
	200	505	395	325	305
	250	270	210	175	165
Alloy E Solder	100	710	555	460	430
	150	475	370	305	285
	200	375	290	240	225
	250	320	250	205	195
Alloy HB Solder	100	1035	805	670	625
	150	710	555	460	430
	200	440	345	285	265
	250	430	335	275	260
Brazing Alloys (melting at or above 1000°F)		Pressure-temperature ratings is that of the tubing being used			

Note: Ratings are those given in ASME B 16.22 "Wrought Copper and Copper Alloy Solder Joint Pressure Fittings." (a) Solder alloys are covered by ASTM Standard Specification B32. The Safe Drinking Water Act Amendment of 1986 prohibits the use of any solder having a lead content in excess of 02% for potable water systems.

PRESSURE LOSS IN FITTINGS EXPRESSED AS EQUIVALENT LENGTH OF TUBE, FEET						
Normal or Standard in Inches	Wrot Copper Fittings					
	90 Degree Ell	45 Degree Ell	Tee Straight Run	Tee Side Branch	Coupling	180 Degree Bend
3/8	0.5	0.5	0.5	1	-	0.5
1/2	0.5	0.5	0.5	1	-	1
5/8	0.5	0.5	0.5	2	-	1
3/4	1	0.5	0.5	2	-	2
1	1	1	0.5	3	-	2
1-1/4	2	1	0.5	4	0.5	3
1-1/2	2	2	1	5	0.5	4
2	2	2	1	7	0.5	8
2-1/2	2	3	2	9	0.5	16
3	3	4	-	-	1	20