

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201 Collierville, Tennessee 38017 United States Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401 United States Phone: 561 273 8300

ITEM # W 01312, FITTING REDUCER, FTG X C, 3/8" X 1/4"

Streamline[®] Copper Solder-Joint Fittings for supply/pressurized systems have been the leading brand of copper fittings for over 80 years. Available in both wrot copper and cast bronze, our product selection has grown to become the most extensive in the industry. We are the acknowledged experts at engineering and manufacturing precision solder-joint copper fittings. Quality, consistency and reliability have made the Streamline[®] brand trusted and specified all around the world.

• For use in above-



<u>Specifications</u> | <u>Dimensions</u> | <u>Details</u>

Specifications	
Weight	0.02 lb
Material	WROT COPPER

+ more

	6/3/2022 Page 2	2 of 2
Operating Temperature	CDA-Copper-Fitting-Pressue-Temp-Ratings	
Operating Pressure	<u>CDA-Copper-Fitting-Pressue-Temp-Ratings</u>	
End Type	FTG - Fitting (Male Solder)	
End Size	3/8 in	
Second End Type	C - Cup (Female Solder)	
Second End Size	1/4 in	
Standards	ASME B16.15 ASME B16.18 ASME B16.22 ASME B16.24 ASME B16.50 ASME B1.20.1	
nensions		-
Overall Length	0.91 in	
Overall Height	0.50 in	
Overall Width	0.50 in	
ails		-
Style	WC-403	
Qty Pcs / Bag	50	
	1700	
Master Qty Pcs / Box	1700	
	Operating Pressure End Type End Size Second End Type Second End Size Standards Overall Length Overall Height Overall Width Style	Operating PressureCDA-Copper-Fitting-Pressue-Temp-RatingsEnd TypeFTG - Fitting (Male Solder)End Size3/8 inSecond End TypeC - Cup (Female Solder)Second End Size1/4 inStandardsASME B16.15 ASME B16.15 ASME B16.22 ASME B16.22

1/2 FTG X 3/80D FTG RED

Mueller Description 2