

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201 Collierville, Tennessee 38017 United States Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401 United States Phone: 561 273 8300

ITEM # W 01232, ADAPTER FEMALE, C X FPT, 1/2" X 3/8"

Streamline[®] Copper Solder-Joint Fittings for supply/pressurized systems have been the leading brand of copper fittings for over 80 years. Available in both wrot copper and cast bronze, our product selection has grown to become the most extensive in the industry. We are the acknowledged experts at engineering and manufacturing precision solder-joint copper fittings. Quality, consistency and reliability have made the Streamline[®] brand trusted and specified all around the world.

• For use in above-



<u>Specifications</u> | <u>Dimensions</u> | <u>Details</u>

Specifications		-
Weight	0.07 lb	
Material	WROT COPPER	

+ more

Operating Temperature CDA-Copper-Fitting-Pressue-Temp-Ratings Operating Pressure CDA-Copper-Fitting-Pressue-Temp-Ratings End Type C - Cup (Female Solder) End Type C - Cup (Female Solder) End Size 1/2 in Second End Type FPT - Female Pipe Tapered Thread, NPT Second End Size 3/8 in Standards SSF B16.15 ASME B16.18 ASME B16.18 ASME B16.22 ASME B16.23 ASME B16.20 ASME B10.20 1 Overall Length 1.29 in Overall Length 0.92 in Overall Width 0.92 in Overall Width 0.92 in			10,02022 1 49	0 2 01 2			
Find Type C - Cup (Female Solder) End Size 1/2 in Second End Type FPT - Female Pipe Tapered Thread, NPT Second End Size 3/8 in NSF 61G ASME B16.15 ASME B16.18 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.24 ASME B16.22 ASME B16.24 ASME B16.24 ASME B16.20 ASME B16.24 ASME B16.24 ASME B16.24 ASME B16.20 ASME B16.24 Overall Length 0.82 in Overall Height 0.92 in Overall Width 0.92 in		Operating Temperature	CDA-Copper-Fitting-Pressue-Temp-Ratings				
End Size1/2 inSecond End TypeFPT - Fenale Pipe Tapered Thread, NPTSecond End Size3/8 inStandardsNSF 61G ASME B16.15 ASME B16.22 ASME B16.22 		Operating Pressure	CDA-Copper-Fitting-Pressue-Temp-Ratings				
second End Type FPT - Female Pipe Tapered Thread, NPT second End Size 3/8 in bread Fadards NSF 61G ASME B16.15 ASME B16.18 ASME B16.22 ASME B16.22 ASME B16.22 ASME B16.20 ASME B12.0.1 - coverall Length 1.29 in - overall Height 0.82 in - coverall Width 0.92 in - coverall Xeight VC402R -		End Type	C - Cup (Female Solder)				
Second End Size3/8 instandardsNSF 61G ASME B16.15 ASME B16.22 ASME B16.22 ASME B16.20.1Standardsoterall Length1.29 inoverall Length0.82 inoverall Width0.92 inoterall Length0.92 in		End Size	1/2 in				
standardsNSF 61G ASME B16.15 ASME B16.22 ASME B16.22 ASME B16.20.1Dimensions-Overall Length1.29 inOverall Height0.82 inOverall Width0.92 inDetails-StyleWC-402R		Second End Type	FPT - Female Pipe Tapered Thread, NPT				
StandardsASME B16.15 ASME B16.22 ASME B16.24 ASME B16.50 ASME B1.20.1-Dimensions-Overall Length1.29 inOverall Height0.82 inOverall Width0.92 inDetails-StyleWC-402R		Second End Size	3/8 in				
Overall Length1.29 inOverall Height0.82 inOverall Width0.92 in		Standards	ASME B16.15 ASME B16.18 ASME B16.22 ASME B16.24 ASME B16.50				
Overall Height0.82 inOverall Width0.92 inOctails-StyleWC-402R	Dimensions –						
overall Width 0.92 in Details Style WC-402R		Overall Length	1.29 in				
Details -		Overall Height	0.82 in				
Style WC-402R		Overall Width	0.92 in				
	Det	ails		-			
Oty Pcs / Bag 50		Style	WC-402R				
		Qty Pcs / Bag	50				

500

1/2 C X 3/8 FPT ADAPTER

5/8 OD X 3/8 FPT ADAPTER

D

Master Qty Pcs / Box

Mueller Description 1

Mueller Description 2