

ProPressG

The ProPress fitting is also available for gas applications. Available with a factory-installed HNBR sealing element, Viega ProPressG fittings are suitable for natural gas and fuel oil applications, among others. Installers can make secure connections in seconds with system-matched tools and jaws. The patented Viega Smart Connect feature, a unique aspect designed into the fittings themselves and only available from Viega, provide installers with increased confidence in the integrity of their connections.

FEATURES AND BENEFITS

- Available in sizes ½" to 2"
- More than 350 engineered fitting configurations for copper
- Approved for more than 150 different applications

CODES AND STANDARDS

- CSA International: Canadian Standards Association
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- IFGC: International Fuel Gas Code
- NFPA 30: Flammable and Combustible Liquids Code
- NFPA 30A: Code for Motor Fuel Dispensing Facilities and Repair Garages
- NFPA 31: Standard for the Installation of Oil-Burning Equipment (supply line only)
- NFPA 54/Z223: National Fuel Gas Code
- NFPA 58: Liquefied Petroleum Gas Code

LISTINGS AND CERTIFICATIONS

- CSA ANSI LC4/CSA 6.32
- IAPMO ANSI LC-4/CSA 6.32
- ICC-ES PMG-1036
- CSA B149.1
- CRN 0A14541.5 A/B/C

NOTE

A Yellow Dot on a Viega ProPressG fitting indicates the Smart Connect feature with a HNBR sealing element.

Elbows



Viega ProPressG 90° elbow

Smart Connect feature

- For use with ASTM B88 tubing
- Copper
- Press connection

Components

HNBR sealing elements

Model 0616

	P1	P2	Wt [lb]	Quantity	Part No	DG
	1/2	1/2	0.112	10	16128	8
	3/4	3/4	0.201	10	16133 ¹	8
New	3/4	3/4	0.173	10	16733 ²	8
	1	1	0.283	10	16138 ¹	8
New	1	1	0.278	10	16738 ²	8
	1 1/4	1 1/4	0.425	1	16143 ¹	8
New	1 1/4	1 1/4	0.381	1	16743 ²	8
	1 1/2	1 1/2	0.815	1	16148 ¹	8
New	1 1/2	1 1/2	0.668	1	16748 ²	8
	2	2	1.157	1	16153 ¹	8
New	2	2	1.055	1	16753 ²	8

¹⁾ Available while supplies last

²⁾ new versions available soon



Viega ProPressG 90° street elbow

Smart Connect feature

- For use with ASTM B88 tubing
- Copper
- Press connection, street

Components

HNBR sealing element

Model 0616.1

	P	FTG	Wt [lb]	Quantity	Part No	DG
	1/2	1/2	0.104	10	16158	8
	3/4	3/4	0.188	10	16163	8
New	3/4	3/4	0.164	10	16763 ²	8
	1	1	0.266	10	16168	8
New	1	1	0.265	10	16768 ²	8
	1 1/4	1 1/4	0.414	1	16173 ¹	8
	1 1/2	1 1/2	0.771	1	16178 ¹	8
	2	2	1.102	1	16183 ¹	8

¹⁾ Available while supplies last

²⁾ new versions available soon



Viega ProPressG 45° elbow

Smart Connect feature

- For use with ASTM B88 tubing
- Copper
- Press connection

Components

HNBR sealing elements

Model 0626

	P1	P2	Wt [lb]	Quantity	Part No	DG
	1/2	1/2	0.095	10	16188	8
	3/4	3/4	0.161	10	16193	8
New	3/4	3/4	0.150	10	16793 ²	8
	1	1	0.223	5	16198 ¹	8
New	1	1	0.210	5	16798 ²	8
	1 1/4	1 1/4	0.324	1	16203	8
	1 1/2	1 1/2	0.626	1	16208	8
	2	2	0.849	1	16213	8

¹⁾ Available while supplies last

²⁾ new versions available soon



Viega ProPressG 45° street elbow

Smart Connect feature

- For use with ASTM B88 tubing
- Copper
- Press connection, street

Components

HNBR sealing element

Model 0626.1

	P	FTG	Wt [lb]	Quantity	Part No	DG
	1/2	1/2	0.083	10	16218	8
	3/4	3/4	0.149	10	16223	8
New	3/4	3/4	0.140	10	16723 ²	8
	1	1	0.209	5	16228	8
	1 1/4	1 1/4	0.315	1	16233 ¹	8
	1 1/2	1 1/2	0.596	1	16238 ¹	8
	2	2	0.824	1	16243 ¹	8

¹⁾ Available while supplies last

²⁾ new versions available soon