

Heating and Cooling Solutions



4.1

viega

Heating and Cooling Solutions

Radiant heating systems have been around since 10,000 B.C., but Viega has made them more efficient, reliable and easier to install. Viega offers a full line of prefabricated Climate Mats for wet installs, panels for dry installs, tubing, manifolds, mixing options and controls engineered to work together. Radiant heating and cooling solutions can reduce energy costs by up to 30% for both residential and commercial buildings. Our hands-on design team can provide you with a complete design and bill of materials, so you know you have everything you need for a properly functioning system.

FEATURES AND BENEFITS

- Faster and easier than traditional radiant installation
- Typically reduces energy costs from 10-30%
- Minimizes circulation of dust, allergens and airborne contaminants
- Proven press technology helps to ensure secure connections
- 30-year warranty on Viega Barrier PEX, FostaPEX and PureFlow Press metal and polymer fittings
- Technical support
- Design and layout services

CODES AND STANDARDS

- CSA B214: Installation Code for Hydronic Heating Systems
- IAPMO: California Mechanical Code (CMC)
- IAPMO: Uniform Mechanical Code (UMC)
- IAPMO: Uniform Solar, Hydronics and Geothermal Code (USHGC)
- ICC: International Mechanical Code (IMC)
- ICC: International Residential Code (IRC)
- International Energy Conservation Code (IECC)
- National Building Code of Canada (NBCC)

LISTINGS AND CERTIFICATIONS

- ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM F876: Standard Specification for Cross-linked Polyethylene (PEX) Tubing
- ASTM F877: Standard Specification for Cross-linked Polyethylene (PEX) Plastic Hot- and Cold-Water Distribution Systems
- ASTM F3253: Standard Specification for Cross-linked Polyethylene (PEX) Tubing with Oxygen Barrier for Hot- and Cold-Water Hydronic Distribution Systems
- ASTM F3347: Standard Specification for Metal Press Insert Fittings with Factory Assembled Stainless Steel Press Sleeve for SDR9 Cross-linked Polyethylene (PEX) Tubing
- ASTM F3348: Standard Specification for Plastic Press Insert Fittings with Factory Assembled Stainless Steel Press Sleeve for SDR9 Cross-linked Polyethylene (PEX) Tubing
- CAN/ULC S101: Standard Methods for Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Methods for Test for Surface Burning Characteristics of Flooring, Floor Coverings, and Miscellaneous Materials and Assemblies
- CSA B137.5: Standard Specification for PEX Tubing in Pressure Applications
- CSA B214: Installation Code for Hydronic Heating Systems
- HUD MR1276: Housing and Urban Development
- IAPMO File 4030 (PureFlow)
- IAPMO File 4874 (FostaPEX)

- ICC-ES LC 1004: PMG Listing Criteria for PP, PEX, PEX-AL-PEX, and PP-AL-PP Piping, Tube and Fittings Used in Radiant
- ICC-ES PMG-1015 (ProRadiant)
- Heating and Water Supply Systems
- NSF/ANSI 14: Plastic Piping Systems Components and Related Materials
- UL 263/ANSI: Safety Fire Tests for Building Construction and Materials

NOTE

A green dot on a Viega PureFlow Press fitting indicates Smart Connect technology.


Adapter

- For Viēga PureFlow Press connections with SVC manifold outlets
- Bronze
- Press connection, SVC

Model 2819NG

P	SVC	Wt [lb]	Quantity	Part No	DG
5/16	✓	0.140	5	89407	4
3/8	✓	0.141	5	89408	4
1/2	✓	0.145	5	89409	4
5/8	✓	0.161	5	89413	4
3/4	✓	0.158	5	89410	4


Compression adapter

- Bronze
- Compression, SVC
- Allows Viēga PEX compression connections with SVC manifold outlets

Components

Adapter, compression ring, nut

Model 1022SV

P	SVC	Wt [lb]	Quantity	Part No	DG
5/16	✓	0.214	2	19007	4
3/8	✓	0.209	2	19008	4
1/2	✓	0.197	2	19009	4
5/8	✓	0.197	2	19010	4


Compression adapter

- Bronze
- Compression, SVC
- Allows Viēga PEX compression connections with SVC manifold outlets

Components

Adapter, compression ring, nut, threaded adapter

Model 1022.1SV

P	SVC	Wt [lb]	Quantity	Part No	DG
3/4	✓	0.371	2	19011	4


SVC compression adapter

- Only for type L copper, type K copper, type M copper
- Brass
- SVC
- Allows compression copper connection with SVC manifold without soldering

Components

Brass nut, plastic insert

Model 9438.5SV

d	SVC	Wt [lb]	Quantity	Part No	DG
1/2	✓	0.087	10	19305	4
3/4	✓	0.321	10	19306	4


SVC adapter

- Bronze
- Male pipe thread, SVC

Model 1022.6SV

MPT	SVC	Wt [lb]	Quantity	Part No	DG
1/2	✓	0.140	5	19109	4
3/4	✓	0.167	5	19110	4


Coupling

- Bronze
- SVC

Model 1022.7SV

SVC1	SVC2	Wt [lb]	Quantity	Part No	DG
✓	✓	0.153	10	19012	4


Strap-on temperature gauge set

- Can be soldered

Components

Gauge, mounting spring, heat transfer paste

Model 2810.3US

d	Temp [°F]	Wt [lb]	Quantity	Part No	DG
2 1/2	32–250	0.260	1	15055	4