

Heating and Cooling Solutions

Radiant heating systems have been around since 10,000 B.C., but Viega has made them more efficient, reliable and easier to install. Viega offers a full line of prefabricated Climate Mats for wet installs, panels for dry installs, tubing, manifolds, mixing options and controls engineered to work together. Radiant heating and cooling solutions can reduce energy costs by up to 30% for both residential and commercial buildings. Our hands-on design team can provide you with a complete design and bill of materials, so you know you have everything you need for a properly functioning system.

FEATURES AND BENEFITS

- Faster and easier than traditional radiant installation
- Typically reduces energy costs from 10-30%
- Minimizes circulation of dust, allergens and airborne contaminants
- Proven press technology helps to ensure secure connections
- 30-year warranty on Viega Barrier PEX, FostaPEX and PureFlow Press metal and polymer fittings
- Technical support
- Design and layout services

CODES AND STANDARDS

- CSA B214: Installation Code for Hydronic Heating Systems
- IAPMO: California Mechanical Code (CMC)
- IAPMO: Uniform Mechanical Code (UMC)
- IAPMO: Uniform Solar, Hydronics and Geothermal Code (USHGC)
- ICC: International Mechanical Code (IMC)
- ICC: International Residential Code (IRC)
- International Energy Conservation Code (IECC)
- National Building Code of Canada (NBCC)

LISTINGS AND CERTIFICATIONS

- ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM F876: Standard Specification for Cross-linked Polyethylene (PEX) Tubing
- ASTM F877: Standard Specification for Cross-linked Polyethylene (PEX) Plastic Hot- and Cold-Water Distribution Systems
- ASTM F3253: Standard Specification for Cross-linked Polyethylene (PEX) Tubing with Oxygen Barrier for Hot- and Cold-Water Hydronic Distribution Systems
- ASTM F3347: Standard Specification for Metal Press Insert Fittings with Factory Assembled Stainless Steel Press Sleeve for SDR9 Cross-linked Polyethylene (PEX) Tubing
- ASTM F3348: Standard Specification for Plastic Press Insert Fittings with Factory Assembled Stainless Steel Press Sleeve for SDR9 Cross-linked Polyethylene (PEX) Tubing
- CAN/ULC S101: Standard Methods for Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Methods for Test for Surface Burning Characteristics of Flooring, Floor Coverings, and Miscellaneous Materials and Assemblies
- CSA B137.5: Standard Specification for PEX Tubing in Pressure Applications
- CSA B214: Installation Code for Hydronic Heating Systems
- HUD MR1276: Housing and Urban Development
- IAPMO File 4030 (PureFlow)
- IAPMO File 4874 (FostaPEX)

- ICC-ES LC 1004: PMG Listing Criteria for PP, PEX, PEX-AL-PEX, and PP-AL-PP Piping, Tube and Fittings Used in Radiant
- ICC-ES PMG-1015 (ProRadiant)
- Heating and Water Supply Systems
- NSF/ANSI 14: Plastic Piping Systems Components and Related Materials
- UL 263/ANSI: Safety Fire Tests for Building Construction and Materials

NOTE

A green dot on a Viega PureFlow Press fitting indicates Smart Connect technology.



RABS - WLAN Module

- Use only with Radiant Auto-Balancing System
- One per control unit

Note

Enables wireless communication to RABS control unit

Model 1250.4US

New

	Wt [lb]	Quantity	Part No	DG
	0.125	1	17070	4



Pump and boiler relay Components

120 VAC supply, 24 VAC transformer, control pump and boiler contact outputs with dry or powered input signal

Model 2876.0US

	Wt [lb]	Quantity	Part No	DG
	1.040	1	18033	4



Digital thermostat

- For sensing floor and/or room temperature
- Suitable for zone control Model 2874.7US, powerhead Model 2877.7
- Adjustable setback, controls up to (4) powerheads, high or low limit protection

Model 2874.5US

V	Wt [lb]	Quantity	Part No	DG
24	0.250	1	18050	4



Floor sensor

Digital thermostat

- Suitable for digital thermostat Model 2874.5US
- 10KΩ

Model 2874.6US

L [ft]	Wt [lb]	Quantity	Part No	DG
10	0.200	1	18051	4



Thermostat

Heat/cool non programmable

- For 1 stage heat / 1 stage cool
- Suitable for zone control Model 2874.7US, powerhead Model 2877.7
- Controls up to (4) powerheads, battery or 24V power

Model 2878.6

V	Wt [lb]	Quantity	Part No	DG
24	0.675	1	15116	4



Thermostat

Heat/cool programmable

- For 1 stage heat / 1 stage cool
- Suitable for zone control Model 2874.7US, powerhead Model 2877.7
- Controls up to (4) powerheads, battery or 24V power

Model 2878.7

V	Wt [lb]	Quantity	Part No	DG
24	0.695	1	15117	4