

PureFlow Press

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water. By combining the highest-rated PEX tubing on the market (according to industry standards) with the revolutionary Viega ManaBloc and press manifolds, as well as press fittings, the Viega PureFlow System saves time, labor and cost. The first press system for the PEX market, Viega PureFlow Press fittings have factory-attached sleeves that improve consistency and reduce installation errors. Available in high-performance polymer and Viega Zero Lead bronze, Viega PureFlow Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions; and system-matched tools and jaws make installation easy and consistent.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled fittings with attached stainless steel sleeves reduce installation errors
- Available in sizes from $\frac{3}{8}$ " to 2"
- The only PEX fittings with Viega Smart Connect technology
- Backed by a 25-year limited warranty

ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.


Viega PureFlow PEX tubing

- PEX

- Coil

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877

Model V5003

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¼	100	white	3.200	1	32011	1
¼	500	white	14.000	1	32015	1
¾	100	white	5.000	1	32001¹	1
¾	500	white	21.000	1	32005¹	1
¾	1000	white	42.000	1	32000	1
½	100	white	6.000	1	32021¹	1
½	300	white	17.100	1	32023¹	1
½	500	white	28.000	1	32025¹	1
½	1000	white	55.000	1	32020¹	1
¾	100	white	11.000	1	32041¹	1
¾	300	white	32.100	1	32043¹	1
¾	500	white	53.000	1	32045¹	1
1	100	white	17.000	1	32061¹	1
1	300	white	51.900	1	32063¹	1
1	500	white	88.000	1	32065	1

¹⁾ center pull coil

Viega PureFlow PEX tubing

- PEX

- Straight length

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877

Model V5003.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	20	white	1.080	50	33020	1
¾	20	white	2.060	25	33045	1
1	20	white	3.420	15	33061	1


Viega PureFlow PEX tubing

- PEX

- Coil

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877

Model V5009

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	100	black	5.500	1	32721	1
½	300	black	16.500	1	32723	1
½	500	black	29.000	1	32725	1


Viega PureFlow PEX tubing

- PEX

- Coil

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877, UL listed for NFPA

13D systems

Model V5009.1

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	100	black	10.500	1	34741	1
¾	300	black	31.500	1	34743	1
¾	500	black	52.500	1	34745	1
1	100	black	17.400	1	34761	1
1	500	black	87.000	1	34765	1
1¼	100	black	25.500	1	34771	1
1¼	300	black	76.500	1	34773	1
1½	100	black	35.400	1	34781	1
2	100	black	63.000	1	32791	1


Viega PureFlow PEX tubing

- PEX

- Straight length

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877

Model V5009.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
½	20	black	1.100	50	33720	1


Viega PureFlow PEX tubing

- PEX

- Straight length

Technical Data

PEX designation code 5306

UV resistance 6 months

ASTM F876, ASTM F877, UL listed for NFPA

13D systems

Model V5009.51

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
¾	20	black	2.100	25	35745	1
1	20	black	1.160	15	35761	1
1¼	20	black	5.100	10	35771	1
1½	20	black	7.060	5	35781	1
2	20	black	12.280	5	33791	1