PureFlow Press

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water. By combining the highest-rated PEX tubing on the market (according to industry standards) with the revolutionary Viega ManaBloc and press manifolds, as well as press fittings, the Viega PureFlow System saves time, labor and cost. The first press system for the PEX market, Viega PureFlow Press fittings have factory-attached sleeves that improve consistency and reduce installation errors. Available in high-performance polymer and Viega Zero Lead bronze, Viega PureFlow Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions; and system-matched tools and jaws make installation easy and consistent.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled fittings with attached stainless steel sleeves reduce installation errors
- Available in sizes from ³/₈" to 2"
- The only PEX fittings with Viega Smart Connect technology
- Backed by a 25-year limited warranty

ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.

V	ie	g	a
	_		

	Viega PureFlow Press adapter Zero Lead	Р	FPT	Wt [lb]	Quantity		DG
· · · · · · · · · · · · · · · · · · ·	- Bronze	1/2	1/2	0.098	10	91520	6
	 Press connection, female pipe thread 	1/2	3⁄4	0.135	10	91525	6
and the second s	Model 2812ZL	3⁄4	1/2	0.110	10	91541	6
		3⁄4	3⁄4	0.141	10	91540	6
		1	3⁄4	0.166	10	91545	6
		1	1	0.239	10	91560	6
		1¼	1¼	0.436	5	91570	6
		1½	1½	0.511	5	91580	6
		2	2	0.818	5	91590	6
	Viega PureFlow Press adapter Zero Lead	Р	С	Wt [lb]	Quantity	Part No	DG
And a state of the	- Bronze	3⁄8	1/2	0.062	10	92006	6
	- Press connection, female copper tube size	1/2	1/2	0.063	10	92021	6
	Model 2813.5ZL	1/2	3⁄4	0.099	10	92026	6
	MODEL 2813.5ZL	3⁄4	1/2	0.067	10	92036	6
		3⁄4	3⁄4	0.113	10	92041	6
		3⁄4	1	0.176	10	92045	6
		1	1	0.186	10	92060	6
		11/4	11/4	0.323	5	92070	6
		1½	1½	0.436	5	92080	6
		2	2	0.655	5	92090	6
~2	Viega PureFlow Press adapter	Р	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
the a	Zero Lead	1/2	1/2	0.064	10	97520	6
and the second s	- Bronze	1/2	3/4	0.004	10	97525	6
	 Press connection, street 	3⁄4	-74 1/2	0.094	10	97535	6
	Note	3/4	3/4	0.101	10	97540	6
	ProPress tool and jaw required	3/4	1	0.154	10	97545	6
	Model 2813.1ZL	1	1	0.175	10	97560	6
		11⁄4	11/4	0.305	5	97570	6
		11/2	11/2	0.436	5	97580	6
		2	2	0.696	5	97590 ¹	6
			older fittings only.	0.000	Ū		Ū
(The second sec	Viega PureFlow Press adapter	Р	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
Eller	Zero Lead	P 2	FTG (CTS) 2	Wt [lb] 0.748	Quantity 5	Part No 976901	DG 6
	Zero Lead - Bronze	2	2	0.748	-		
	Zero Lead	2		0.748	-		
	Zero Lead - Bronze - Press connection <u>Note</u> 2" ProPress tool and jaw required Model 2813.3ZL	2 ¹⁾ for use with V	2 Viega ProPress fitting	0.748 gs only.	5	97690 ¹	6
	Zero Lead - Bronze - Press connection <u>Note</u> 2" ProPress tool and jaw required	2 ¹⁾ for use with V	2 /iega ProPress fitting PB	0.748 gs only. Wt [lb]	5 Quantity	97690 ¹ Part No	6 DG
	Zero Lead - Bronze - Press connection <u>Note</u> 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter	2 ¹⁾ for use with V P 1/2	2 Viega ProPress fitting PB ½	0.748 gs only. Wt [lb] 0.049	5 Quantity 10	97690 ¹ Part No 97820	6 DG 6
	Zero Lead - Bronze - Press connection <u>Note</u> 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead	2 ¹⁾ for use with V	2 /iega ProPress fitting PB	0.748 gs only. Wt [lb]	5 Quantity	97690 ¹ Part No	6 DG
	Zero Lead - Bronze - Press connection <u>Note</u> 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze	2 ¹⁾ for use with V P 1/2	2 Viega ProPress fitting PB ½	0.748 gs only. Wt [lb] 0.049	5 Quantity 10	97690 ¹ Part No 97820	6 DG 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter	2 ¹⁾ for use with V P 1/2 3/4	2 Viega ProPress fitting PB 1/2 3/4	0.748 gs only. Wt [lb] 0.049 0.072	Quantity 10 10	97690 ¹ Part No 97820 97840	6 DG 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead	2 ¹⁾ for use with V P 1/2 3/4	2 Viega ProPress fitting PB ½ 3/4	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb]	5 Quantity 10 10	976901 Part No 97820 97840 Part No	6 DG 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze	2 ¹⁾ for use with V P 1/2 3/4 P 3/4	2 Viega ProPress fitting PB ½ 3/4 Flare 3/4	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275	5 Quantity 10 10 Vuantity 10	976901 Part No 97820 97840 Part No 97140	6 DG 6 6 5
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze - Bronze - Bronze - Bronze - Press connection, flare connection	2 ¹⁾ for use with V P 1/2 3/4 P 3/4 1	2 Viega ProPress fitting PB ½ 34 Flare 34 34	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275 0.327	5 Quantity 10 10 Quantity 10 10	976901 Part No 97820 97840 Part No 97140 97160	6 DG 6 6 6 6 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze	2 ¹⁾ for use with V P 1/2 3/4 P 3/4	2 Viega ProPress fitting PB ½ 3/4 Flare 3/4	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275	5 Quantity 10 10 Vuantity 10	976901 Part No 97820 97840 Part No 97140	6 DG 6 6 5
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze - Bronze - Bronze - Press connection, flare connection Model 2892ZL	2 ¹⁾ for use with V P 1/2 3/4 1 1	2 Viega ProPress fitting PB 1/2 3/4 Flare 3/4 3/4 1	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275 0.327 0.414	5 Quantity 10 10 10 10 10 10	976901 Part No 97820 97840 97840 97840 97140 97140 97165	6 DG 6 6 6 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze - Bronze - Bronze - Bronze - Press connection, flare connection	2 ¹⁾ for use with V P ¹ /2 ³ /4 ¹ 1 P	2 Viega ProPress fitting PB ½ 34 Flare 34 34	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275 0.327	5 Quantity 10 10 Quantity 10 10	976901 Part No 97820 97840 97840 97840 97140 97140 97165	6 DG 6 6 6 6 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, flare connection Model 2892ZL Viega PureFlow Press tailpiece Zero Lead	2 ¹⁾ for use with V P 1/2 3/4 1 1	2 Viega ProPress fitting PB 1/2 3/4 Flare 3/4 3/4 1	0.748 gs only. Wt [lb] 0.049 0.072 Wt [lb] 0.275 0.327 0.414	5 Quantity 10 10 10 10 10 10	976901 Part No 97820 97840 97840 97840 97140 97140 97165	6 DG 6 6 6 6 6
	Zero Lead - Bronze - Press connection Note 2" ProPress tool and jaw required Model 2813.3ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, polybutylene (PB) connection Note Ring not included Model 2813.2ZL Viega PureFlow Press adapter Zero Lead - Bronze - Press connection, flare connection Model 2892ZL Viega PureFlow Press tailpiece	2 ¹⁾ for use with V P ¹ /2 ³ /4 ¹ 1 P	2 Viega ProPress fitting PB 1/2 3/4 3/4 1 1 F BSP	0.748 gs only. Wt [Ib] 0.049 0.072 Wt [Ib] 0.275 0.327 0.414 Wt [Ib]	5 Quantity 10 10 10 10 10 10 10	976901 Part No 97820 97840 97840 97160 97160 97165 Part No	6 DG 6 6 6 6 6 6 6