

PureFlow Crimp

With the reliability and quality required for potable water, Viega PureFlow Crimp fittings are part of Viega's complete plumbing solution. Matched with the revolutionary Viega ManaBloc water distribution system and the highest-rated PEX tubing in the industry (according to industry standards), Viega PureFlow Crimp fittings are a time-tested method for joining PEX.

FEATURES AND BENEFITS

- EcoBrass fittings provide better corrosion resistance than other brass fittings
- High-performance polyalloy fittings are made in the USA
- Peace of mind from durable materials and quality manufacturing
- Available in sizes $\frac{3}{8}$ " to 1"
- Backed by a 25-year limited warranty

ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. Crimp rings are not sold with any PureFlow Crimp product unless otherwise specified.


**Viega PureFlow Crimp adapter
Zero Lead**

- Brass
- Crimp connection, polyethylene (PE) connection

Note

Use standard stainless steel hose clamp for PE connection (not included)

Model V5047ZL

Crimp	PE	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.111	25	46145	2
1	1	0.166	10	46156	2


**Viega PureFlow Crimp adapter
Zero Lead**

- Brass
- Crimp connection, female copper tube size

Model V5045ZL

Crimp	C	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.035	50	46635	2
3/4	3/4	0.082	25	46645	2
1	1	0.108	10	40655¹	2

¹⁾ copper


**Viega PureFlow Crimp adapter
Zero Lead**

- Brass
- Crimp connection, street

Model V5046ZL

Crimp	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.038	50	46633	2
3/4	3/4	0.067	25	46644	2
1	1	0.103	10	60651¹	2

¹⁾ copper


**Viega PureFlow Crimp adapter
Zero Lead**

- Brass
- Crimp connection, female copper tube size, street

Note

Copper connection can be used as either male or female connection.

Model V5024ZL

Crimp	C	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
3/8	3/8	1/2	0.036	50	46622	2
1	3/4	1	0.184	10	46654	2

Couplings


**Viega PureFlow Crimp coupling
Zero Lead**

- Brass
- Crimp connection

Model V5015ZL

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.020	100	46422	2
1/2	3/8	0.025	100	46432	2
1/2	1/2	0.026	100	46434	2
3/4	1/2	0.044	50	46441	2
3/4	3/4	0.047	50	46444	2
1	3/4	0.074	10	46454	2
1	1	0.082	10	46455	2


Viega PureFlow Crimp coupling

- PolyAlloy
- Crimp connection

Model V5215

Crimp1	Crimp2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.006	800	43033	3
3/4	3/4	0.012	500	43044	3
3/4	1/2	0.010	500	43043	3
3/8	3/8	0.004	50	43402	3
1/2	1/2	0.006	100	43403	3
1/2	3/8	0.006	50	43332	3
3/4	1/2	0.010	50	43343	3
3/4	3/4	0.012	50	43404	3
1	1/2	0.019	10	43353	3
1	3/4	0.021	10	43354	3
1	1	0.024	10	43355	3


Viega PureFlow Crimp test plug

- PLS
- Crimp connection

Model V5058

Crimp	Wt [lb]	Quantity	Part No	DG
3/8	0.003	100	43702	3
1/2	0.004	100	43723	3
3/4	0.007	50	43744	3
1	0.015	50	43765	3