



Shutoff valve
 - Brass
 - Female copper tube size, press connection
Model 2834.6US

C	P	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.252	10	17260	4
3/4	5/8	0.434	10	17261	4
3/4	3/4	0.424	10	17262	4



Shutoff / balancing valve
 - Brass
 - Female copper tube size, press connection
Model 2834.7US

P	C	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.514	10	17263	4
5/8	3/4	0.739	10	17264	4
3/4	3/4	0.725	10	17265	4



Shutoff valve
 - Brass
 - Female copper tube size, compression
Model 2834.3US

C	Comp	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.390	10	17166	4
3/4	5/8	0.650	10	17167	4



Closing cap
 - For use with copper manifolds
 - Type L copper
 - Female copper tube size, female pipe thread
Note
 1/2" FPT for draw-off (purge valve) and 1/8" FPT for automatic air vent (bottle vent).
Model 2834.5US

C	FPT1	FPT2	Wt [lb]	Quantity	Part No	DG
1	1/2	1/8	0.400	1	17144	4
1 1/2	1/2	1/8	0.665	1	17125	4
2	1/2	1/8	0.750	1	17106	4



Manifold bracket
 - For use with copper manifolds
 - Galvanized steel
Model 2878.927

d	Wt [lb]	Quantity	Part No	DG
1	0.348	2	17145	4
1 1/2	0.505	1	17126	4
2	0.545	1	17107	4



Manifold cabinet
 - Suitable for manifold Model 2804, 2879
 - Galvanized steel, epoxy powder-coated finish
Model 2879.6US

W [in]	H [in]	D [in]	Wt [lb]	Quantity	Part No	DG
21	30	4 1/2	25.993	1	15800	4
27	30	4 1/2	31.991	1	15801	4
45	30	4 1/2	45.987	1	15802	4



Lock assembly
 - Suitable for manifold cabinet
 Model 2879.6US
Components
 (2) keys
Note
 Part No 15802 requires two locks.
Model 2857.7US

Wt [lb]	Quantity	Part No	DG
0.119	1	15217	4

Controls



Basic heating control
 - For controlling system water temperature based on outdoor reset
 - Modulating mixing valve control, boiler activation
Components
 Supply sensor, outdoor sensor
Model 2871.0US

Wt [lb]	Quantity	Part No	DG
2.488	1	16015	4