



Viega MegaPress 316 3-piece ball valve
Smart Connect technology

- 316 stainless steel
 - Press connections
- Components
EPDM sealing elements, 304 locking handle
Model 5175.8

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	1.717	1	86530	14
3/4	3/4	2.336	1	86535	14
1	1	3.714	1	86540	14
1 1/4	1 1/4	7.172	1	86545	14
1 1/2	1 1/2	8.265	1	86550	14
2	2	8.772	1	86555	14



Viega MegaPress 316 3-piece ball valve
Smart Connect technology

- For use with Sch. 5 to Sch. 40 stainless steel pipe
 - 316 stainless steel
 - Press connections
- Components
EPDM sealing elements, 304 locking handle
Model 5175.8XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	12.761	1	86665	14
3	3	25.126	1	86670	14
4	4	40.113	1	86675	14

Check valves



Viega ProPress check valve
Smart Connect technology

- Zero Lead**
- For potable water applications
 - Bronze
 - Press connection
 - Inline
- Components
EPDM sealing elements
Model 2974ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.180	1	79035	8
3/4	3/4	0.280	1	79040	8
1	1	0.454	1	79045	8
1 1/4	1 1/4	0.639	1	79050	8
1 1/2	1 1/2	0.961	1	79055	8
2	2	1.873	1	79060	8

Butterfly valves



Viega ProPress butterfly valve

- For non-potable application
 - Suitable for Viega ProPress bolt set
Model 2873.89
 - Ductile iron
 - Lug style
- Components
Stainless steel disc and stem, EPDM liner
Model 2873.81

d	BP	Wt [lb]	Quantity	Part No	DG
2 1/2	4	8.283	1	22074	8
3	4	8.887	1	22075	8
4	8	14.656	1	22076	8

BP = bolt pattern

Balancing valves



Viega automatic recirculation balancing valve
Zero Lead

- For automatic balancing of hot water recirculation
 - Suitable for Viega PureFlow Press tailpiece
Model 2893ZL, Viega ProPress tailpiece
Model 2957ZL
 - Bronze
 - Male BSP
- Components
Stainless steel ball
- Technical Data
Operating pressure 150 psi
Operating temperature 180° F
- Note
Integrated isolation
Adjustable setpoint
Adjustable bypass
Model 2981.3ZL

BSP Thread	Wt [lb]	Quantity	Part No	DG
1 x 1	1.159	1	79901	8