


Viega ProPress tee
Smart Connect technology

- For use with Viega ProPress stainless tubing
- 316 stainless steel
- Press connection

Components

EPDM sealing elements

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 4018XL

P1	P2	P3	Wt [lb]	Quantity	Part No	DG
2½	2	1½	1.554	1	80753	9
2½	2	2	1.737	1	80752	9
2½	2½	1½	1.573	1	80751	9
2½	2½	2	1.739	1	80760	9
2½	2½	2½	2.056	1	80610	9
3	3	1¼	1.836	1	80782	9
3	3	1½	1.955	1	80781	9
3	3	2	2.151	1	80770	9
3	3	2½	2.471	1	80780	9
3	3	3	2.722	1	80615	9
4	4	1½	2.733	1	80791	9
4	4	2	3.019	1	80790	9
4	4	2½	3.366	1	80800	9
4	4	3	3.659	1	80810	9
4	4	4	4.212	1	80620	9


Viega ProPress reducing tee
Smart Connect technology

- For use with Viega ProPress stainless tubing
- 316 stainless steel
- Press connection, female pipe thread

Components

EPDM sealing elements

Model 4017.2

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
¾	¾	½	0.287	5	80820	9
¾	¾	¾	0.342	5	80830	9
1	1	½	0.351	5	80840	9
1	1	¾	0.392	5	80850	9
1¼	1¼	½	0.384	1	80860	9
1¼	1¼	¾	0.451	1	80870	9
1¼	1¼	1	0.564	1	80880	9
1½	1½	½	0.708	1	80890	9
1½	1½	¾	0.757	1	80900	9
1½	1½	1	0.840	1	80910	9
2	2	½	0.745	1	80920	9
2	2	¾	0.782	1	80930	9
2	2	1	1.126	1	80940	9


Viega ProPress reducing tee
Smart Connect technology

- For use with Viega ProPress stainless tubing
- 316 stainless steel
- Press connection, female pipe thread

Components

EPDM sealing elements

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 4017.2XL

P1	P2	FPT	Wt [lb]	Quantity	Part No	DG
2½	2½	¾	1.408	1	80950	9
2½	2½	1	1.494	1	80960	9
3	3	¾	1.803	1	80970	9
3	3	1	1.873	1	80980	9
4	4	¾	2.552	1	80990	9
4	4	1	2.667	1	81000	9

Adapters


Viega ProPress adapter
Smart Connect technology

- For use with Viega ProPress stainless tubing
- 316 stainless steel
- Press connection, male pipe thread

Components

EPDM sealing element

Model 4011

P	MPT	Wt [lb]	Quantity	Part No	DG
½	½	0.117	10	80010	9
½	¾	0.170	10	80015	9
¾	½	0.152	10	80020	9
¾	¾	0.185	10	80025	9
¾	1	0.441	5	80030	9
1	¾	0.200	5	80035	9
1	1	0.317	5	80040	9
1¼	1¼	0.588	1	80045	9
1½	1½	0.723	1	80050	9
2	2	0.990	1	80055	9