



Viega MegaPress coupling
No stop
Smart Connect technology
 - For use with Sch.5 to Sch.40 carbon steel pipe
 - Carbon steel
 - Press connection
Components
 FKM sealing elements
Model 5915.5

P1	P2	Wt [lb]	Quantity	Part No	DG
½	½	0.261	10	84130	12
¾	¾	0.344	10	84135	12
1	1	0.533	5	84140	12
1¼	1¼	0.873	1	84145	12
1½	1½	1.155	1	84150	12
2	2	1.471	1	84155	12



Viega MegaPress coupling
No stop
Smart Connect technology
 - For use with Sch.5 to Sch.40 carbon steel pipe
 - Carbon steel
 - Press connection
Components
 FKM sealing elements
Note
 Must be installed with MegaPress XL rings and PressBooster/Z3 actuator
Model 4815.5XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2½	2½	1.668	1	26685	12
3	3	2.374	1	26690	12
4	4	3.945	1	26695	12

Reducers



Viega MegaPress reducer
Smart Connect technology
 - For use with Sch.5 to Sch.40 carbon steel pipe
 - Carbon steel
 - Street, press connection
Components
 FKM sealing element
Model 5915.1

FTG (IPS)	P	Wt [lb]	Quantity	Part No	DG
¾	½	0.273	5	84160	12
1	½	0.370	5	84165	12
1	¾	0.403	5	84170	12
1¼	¾	0.641	1	84175	12
1¼	1	0.699	1	84180	12
1½	¾	0.741	1	84185	12
1½	1	0.815	1	84190	12
1½	1¼	0.946	1	84195	12
2	1	1.016	1	84200	12
2	1¼	1.206	1	84205	12
2	1½	1.311	1	84210	12



Viega MegaPress reducer
Smart Connect technology
 - For use with Sch.5 to Sch.40 carbon steel pipe
 - Carbon steel
 - Street, press connection
Components
 FKM sealing element
Note
 Must be installed with MegaPress XL rings and PressBooster/Z3 actuator
Model 4815.1XL

FTG (IPS)	P	Wt [lb]	Quantity	Part No	DG
2½	1	1.181	1	26700	12
2½	1¼	1.305	1	26705	12
2½	1½	1.411	1	26710	12
2½	2	1.492	1	26715	12
3	1¼	1.770	1	26720	12
3	1½	1.880	1	26725	12
3	2	1.970	1	26730	12
3	2½	2.206	1	26735	12
4	1½	3.075	1	26740	12
4	2	3.110	1	26745	12
4	2½	3.037	1	26750	12
4	3	3.262	1	26755	12

Branch connectors



Viega MegaPress Press-In Branch Connector
 - For use with Sch.10 carbon steel pipe only
 - Carbon steel
 - Press connection, female pipe thread
Components
 FKM sealing element
Model 4812.2

for d	FPT	Wt [lb]	Quantity	Part No	DG
1½	¾	0.454	1	26800	12
2	¾	0.452	1	26805	12
2½	¾	0.458	1	26810	12
3	¾	0.452	1	26815	12
4	¾	0.445	1	26820	12
6	¾	0.441	1	26825	12