

## Zero Lead Bronze Ball Valve - P x Hose Model 2971.6ZL



Part No.	Size (in)
79875	1/2
79876	3/4

- Smart Connect technology
- 250 CWP
- Body: Two Piece Zero Lead Bronze
- Ball: Full Port 316 Stainless Steel
- Stem: Blowout-Proof Eco Brass
- Sealing Element: EPDM
- Listings: APMO/ANSI Z1157, NSF®-61-372, NSF®-U.P. Code, Listed by NSF to Commercial Hot
- Conforms to: MSS SP-110
- Parameters:  
250 psi Maximum Working Pressure  
0°F to 250°F Operating Temperature

## Bronze Ball Valve - P x P - Model 2973



Part No.	Size (in)
24000	1/2
24005	3/4
24010	1
24015	1 1/4
24020	1 1/2
24025	2

- Smart Connect technology
- 250 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO/ANSI Z1157
- Conforms to: MSS SP-110
- Parameters:  
250 psi Maximum Working Pressure  
0°F to 200°F Operating Temperature

## Bronze Ball Valve - P x FPT Model 2973.1



Part No.	Size (in)
24030	1/2
24035	3/4
24040	1

- Smart Connect technology
- 250 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO/ANSI Z1157
- Conforms to: MSS SP-110
- Parameters:  
250 psi Maximum Working Pressure  
0°F to 200°F Operating Temperature

## Bronze Ball Valve - P x Hose Model 2973.3



Part No.	Size (in)
24090	1/2
24095	3/4

- Smart Connect technology
- 250 CWP
- Body: Brass Body with Bronze Connections
- Ball: Full Port Chrome Plated Brass
- Stem: Blowout-Proof Brass
- Sealing Element: EPDM
- Listings: U.P. Code, IAPMO/ANSI Z1157
- Conforms to: MSS SP-110
- Parameters:  
250 psi Maximum Working Pressure  
0°F to 200°F Operating Temperature

## 316 Stainless Steel Ball Valve - P x P Model 4070



Part No.	Size (in)
81080	1/2
81085	3/4
81090	1
81095	1 1/4
81100	1 1/2
81105	2

- Smart Connect technology
- Body: 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: EPDM
- Listings: NSF-61-372
- Conforms to: MSS SP-110
- Parameters:  
200 psi Maximum Working Pressure  
0°F to 250°F Operating Temperature

## 316 Stainless Steel Three Piece Ball Valve P x P - Model 4370.8



Part No.	Size (in)
85132	1/2
85133	3/4
85134	1
85136	1 1/4
85137	1 1/2
85138	2

- Smart Connect technology
- Body: Three Piece 316 Stainless Steel
- Ball: 316 Stainless Steel Fullport
- Stem: Blow-out Proof 316 Stainless Steel
- Sealing Element: FKM
- Conforms to: MSS SP-110
- Parameters:  
200 psi Maximum Working Pressure  
0°F to 250°F Operating Temperature