

## PureFlow Press

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water. By combining the highest-rated PEX tubing on the market (according to industry standards) with the revolutionary Viega ManaBloc and press manifolds, as well as press fittings, the Viega PureFlow System saves time, labor and cost. The first press system for the PEX market, Viega PureFlow Press fittings have factory-attached sleeves that improve consistency and reduce installation errors. Available in high-performance polymer and Viega Zero Lead bronze, Viega PureFlow Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions; and system-matched tools and jaws make installation easy and consistent.

### FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled fittings with attached stainless steel sleeves reduce installation errors
- Available in sizes from  $\frac{3}{8}$ " to 2"
- The only PEX fittings with Viega Smart Connect technology
- Backed by a 25-year limited warranty

### ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

### NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection, female pipe thread  
**Model 2812ZL**

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.098	10	91520	6
1/2	3/4	0.135	10	91525	6
3/4	1/2	0.110	10	91541	6
3/4	3/4	0.141	10	91540	6
1	3/4	0.166	10	91545	6
1	1	0.239	10	91560	6
1 1/4	1 1/4	0.436	5	91570	6
1 1/2	1 1/2	0.511	5	91580	6
2	2	0.818	5	91590	6



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection, female copper tube size  
**Model 2813.5ZL**

P	C	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.062	10	92006	6
1/2	1/2	0.063	10	92021	6
1/2	3/4	0.099	10	92026	6
3/4	1/2	0.067	10	92036	6
3/4	3/4	0.113	10	92041	6
3/4	1	0.176	10	92045	6
1	1	0.186	10	92060	6
1 1/4	1 1/4	0.323	5	92070	6
1 1/2	1 1/2	0.436	5	92080	6
2	2	0.655	5	92090	6



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection, street  
Note  
ProPress tool and jaw required  
**Model 2813.1ZL**

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.064	10	97520	6
1/2	3/4	0.094	10	97525	6
3/4	1/2	0.079	10	97535	6
3/4	3/4	0.101	10	97540	6
3/4	1	0.154	10	97545	6
1	1	0.175	10	97560	6
1 1/4	1 1/4	0.305	5	97570	6
1 1/2	1 1/2	0.436	5	97580	6
2	2	0.696	5	97590 <sup>1</sup>	6

<sup>1)</sup> for use with solder fittings only.



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection  
Note  
2" ProPress tool and jaw required  
**Model 2813.3ZL**

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
2	2	0.748	5	97690 <sup>1</sup>	6

<sup>1)</sup> for use with Viega ProPress fittings only.



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection, polybutylene (PB)  
connection  
Note  
Ring not included  
**Model 2813.2ZL**

P	PB	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.049	10	97820	6
3/4	3/4	0.072	10	97840	6



**Viega PureFlow Press adapter  
Zero Lead**  
- Bronze  
- Press connection, flare connection  
**Model 2892ZL**

P	Flare	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.275	10	97140	6
1	3/4	0.327	10	97160	6
1	1	0.414	10	97165	6



**Viega PureFlow Press tailpiece  
Zero Lead**  
- Bronze  
- Press connection, female union BSP  
**Model 2893ZL**

P	F BSP	Wt [lb]	Quantity	Part No	DG
3/4	1	0.195	10	96140	6
1	1	0.240	10	96160	6
1	1 1/4	0.343	10	96165	6