

Tubing



Viega PureFlow PEX tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101¹	1
3/8	500	red	21.000	1	32105¹	1
1/2	100	red	5.800	1	32121¹	1
1/2	300	red	17.100	1	32123¹	1
1/2	500	red	28.000	1	32125¹	1
1/2	1000	red	58.000	1	32120¹	1
3/4	100	red	11.000	1	32141¹	1
3/4	300	red	32.100	1	32143¹	1
3/4	500	red	53.000	1	32145¹	1
1	100	red	16.900	1	33323¹	1
1	300	red	50.700	1	32163¹	1
1	500	red	88.000	1	32165	1

¹⁾ center pull coil



Viega PureFlow PEX tubing

- PEX
- Straight length

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	20	red	1.060	50	33120	1
3/4	20	red	2.040	25	33145	1
1	20	red	3.420	15	33270	1



Viega PureFlow PEX tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201¹	1
3/8	500	blue	21.000	1	32205¹	1
1/2	100	blue	5.300	1	32221¹	1
1/2	300	blue	17.100	1	32223¹	1
1/2	500	blue	26.500	1	32225¹	1
1/2	1000	blue	55.000	1	32220¹	1
3/4	100	blue	11.000	1	32241¹	1
3/4	300	blue	32.100	1	32243¹	1
3/4	500	blue	53.000	1	32245¹	1
1	100	blue	17.000	1	32266¹	1
1	300	blue	50.700	1	32263¹	1
1	500	blue	88.000	1	32265	1

¹⁾ center pull coil



Viega PureFlow PEX tubing

- PEX
- Straight length

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	20	blue	1.060	50	33240	1
3/4	20	blue	2.040	25	33265	1
1	20	blue	3.420	15	33271	1



Viega PureFlow PEX tubing

- For installation between studs
- PEX
- ManaPac

Components

Recycled plastic reels

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5004

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1