

ProPress

Viega ProPress is the trusted copper press joining solution. Since its introduction in 1999, it has reduced overall job costs, saved time, and increased reliability on jobsites across the globe. Viega ProPress fittings offer Smart Connect technology to provide installers added confidence in their ability to ensure secure connections. With system-matched tools, rings and jaws, press connections are made in seconds, making Viega ProPress suitable for virtually any type of project.

FEATURES AND BENEFITS

- Available in sizes ½" to 4"
- Customizable with three sealing elements: EPDM, HNBR and FKM
- More than 400 engineered fitting configurations for copper and Zero Lead bronze from ½" to 4"
- Approved for more than 250 different applications

ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot indicates an EPDM sealing element.



Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead
 - For transitioning between Viega PureFlow Press and Viega ProPress
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Note
 ProPress and PureFlow tool and jaws required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6

Reducers



Viega ProPress reducer
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection
Components
 EPDM sealing elements
Model 2915.2

P1	P2	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.126	10	78147	8
1	1/2	0.170	10	15603	8
1	3/4	0.175	10	78152	8
1 1/4	3/4	0.244	1	15593	8
1 1/4	1	0.250	1	78157	8
1 1/2	3/4	0.402	1	18473	8
1 1/2	1	0.403	1	15588	8
1 1/2	1 1/4	0.410	1	78162	8
2	3/4	0.553	1	18468	8
2	1	0.583	1	15608	8
2	1 1/4	0.553	1	22328	8
2	1 1/2	0.635	1	78167	8



Viega ProPress reducer
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection
Components
 EPDM sealing elements
Note
 Must be installed with Viega ProPress XL-C rings and V2 actuator.
Model 0915.2XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2 1/2	1	0.827	1	20685	8
2 1/2	1 1/4	0.851	1	20690	8
2 1/2	1 1/2	0.985	1	20695	8
2 1/2	2	1.047	1	20700	8
3	1 1/2	1.245	1	20705	8
3	2	1.289	1	20710	8
3	2 1/2	1.510	1	20715	8
4	2	2.089	1	20720	8
4	2 1/2	2.332	1	20725	8
4	3	2.482	1	20730	8



Viega ProPress reducer
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Street, press connection
Components
 EPDM sealing element
Model 2915.1

FTG (CTS)	P	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.097	10	78077	8
1	1/2	0.127	10	78082	8
1	3/4	0.144	10	78087	8
1 1/4	1/2	0.171	5	22333	8
1 1/4	3/4	0.195	5	78092	8
1 1/4	1	0.190	5	78097	8
1 1/2	3/4	0.277	1	14543	8
1 1/2	1	0.284	1	78102	8
1 1/2	1 1/4	0.304	1	78107	8
2	1	0.406	1	78112	8
2	1 1/4	0.418	1	78117	8
2	1 1/2	0.596	1	78122	8



Viega ProPress reducer
Smart Connect technology
Zero Lead
 - For use with ASTM B88 and B75 tubing
 - Bronze
 - Street, press connection
Components
 EPDM sealing element
Model 2915.1ZL

FTG (CTS)	P	Wt [lb]	Quantity	Part No	DG
1 1/2	1/2	0.325	5	79850	8
2	1/2	0.527	1	79855	8
2	3/4	0.521	1	79860	8

PureFlow Press

Known for forward-thinking system solutions, Viega offers complete plumbing systems for potable water. By combining the highest-rated PEX tubing on the market (according to industry standards) with the revolutionary Viega ManaBloc and press manifolds, as well as press fittings, the Viega PureFlow System saves time, labor and cost. The first press system for the PEX market, Viega PureFlow Press fittings have factory-attached sleeves that improve consistency and reduce installation errors. Available in high-performance polymer and Viega Zero Lead bronze, Viega PureFlow Press fittings are ideal for residential and commercial jobs. Viega also offers fittings for easy copper-to-PEX transitions; and system-matched tools and jaws make installation easy and consistent.

FEATURES AND BENEFITS

- The original press fitting for PEX tubing
- Factory-assembled fittings with attached stainless steel sleeves reduce installation errors
- Available in sizes from 3/8" to 2"
- The only PEX fittings with Viega Smart Connect technology
- Backed by a 25-year limited warranty

ZERO LEAD

Zero Lead identifies Viega products meeting the lead-free requirements of NSF 61-G through testing under NSF/ANSI 372 (0.25% or less maximum weighted average lead content).

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.

Couplings



Viega PureFlow Press coupling
Zero Lead
 - Bronze
 - Press connection
Model 2815ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.041	10	93000	6
1/2	3/8	0.048	10	93005	6
1/2	1/2	0.052	10	93020	6
3/4	1/2	0.070	10	93050	6
3/4	3/4	0.073	10	93040	6
1	3/4	0.113	10	93055	6
1	1	0.131	10	93060	6
1 1/4	3/4	0.187	5	93071	6
1 1/4	1	0.210	5	93065	6
1 1/4	1 1/4	0.260	5	93070	6
1 1/2	3/4	0.238	5	93072	6
1 1/2	1	0.246	5	93073	6
1 1/2	1 1/4	0.289	5	93075	6
1 1/2	1 1/2	0.317	5	93080	6
2	1 1/2	0.491	5	93091	6
2	2	0.573	5	93090	6



Viega PureFlow Press coupling
Smart Connect technology
 - Polymer
 - Press connection
Model V5615

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.022	25	49402	6
1/2	3/8	0.024	25	49342	6
1/2	1/2	0.027	25	49403	6
3/4	1/2	0.034	25	49343	6
3/4	3/4	0.040	25	49404	6
1	3/4	0.055	10	49354	6
1	1	0.068	10	49405	6
1 1/4	3/4	0.101	5	49347	6
1 1/4	1	0.112	5	49357	6
1 1/4	1 1/4	0.151	5	49407	6
1 1/2	3/4	0.118	5	49348	6
1 1/2	1	0.133	5	49358	6
1 1/2	1 1/4	0.165	5	49378	6
1 1/2	1 1/2	0.190	5	49408	6
2	1 1/2	0.270	1	49398	6
2	2	0.305	1	49409	6



Viega PureFlow Press test plug
Smart Connect technology
 - Polymer
 - Press connection
Model V5656

P	Wt [lb]	Quantity	Part No	DG
3/8	0.011	25	49722	6
1/2	0.015	25	49723	6
3/4	0.022	25	49744	6
1	0.038	10	49765	6
1 1/4	0.082	5	49770	6
1 1/2	0.095	5	49780	6
2	0.154	1	49790	6



Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead
 - For transitioning between Viega PureFlow Press and Viega ProPress
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Note
 ProPress and PureFlow tool and jaws required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6

3.1

Heating and Cooling Solutions

Radiant heating systems have been around since 10,000 B.C., but Viega has made them more efficient, reliable and easier to install. Viega offers a full line of prefabricated Climate Mats for wet installs, panels for dry installs, tubing, manifolds, mixing options and controls all engineered to work together. Radiant heating and cooling solutions can reduce energy costs by up to 30% for both residential and commercial buildings. Our hands-on design team can provide you with a complete design and bill of materials, so you know you have everything you need for a properly functioning system.

FEATURES AND BENEFITS

- Faster and easier than traditional radiant installation
- Typically reduces energy costs from 10-30%
- Minimizes circulation of dust, allergens and airborne contaminants
- Proven press technology helps to ensure secure connections
- Backed by a 30-year warranty on Viega Barrier PEX, PureFlow Press metal and polymer fittings
- Technical support
- Design and layout services

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.



Viega PureFlow Press adapter
Zero Lead
 - Bronze
 - Press connection, female pipe thread
Model 2812ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.098	10	91520	6
1/2	3/4	0.135	10	91525	6
3/4	1/2	0.110	10	91541	6
3/4	3/4	0.141	10	91540	6
1	3/4	0.166	10	91545	6
1	1	0.239	10	91560	6
1 1/4	1 1/4	0.436	5	91570	6
1 1/2	1 1/2	0.511	5	91580	6
2	2	0.818	5	91590	6



Viega PureFlow Press adapter
Smart Connect technology
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Model 2813PNG

P1	P2	Wt [lb]	Quantity	Part No	DG
5/8	1/2	0.081	5	69627	4
5/8	3/4	0.134	5	69628	4



Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead
 - For transitioning between Viega PureFlow Press and Viega ProPress
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Note
 ProPress and PureFlow tool and jaws required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6



Viega ProPress 90° extended street elbow
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection, street
Components
 EPDM sealing element
Model 2947

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.386	5	77353*	8

* = Available while supplies last



Viega ProPress insert stiffener
 - For Viega ProPress 90° extended street elbow
 - Suitable for Viega ProPress 90° extended street elbow Model 2947
 - Bronze
Model 2946

d	Wt [lb]	Quantity	Part No	DG
3/4	0.046	5	16423	4



Viega PureFlow Press adapter
 - Bronze
 - Press connection, female copper tube size
Model 2813.5NG

P	C	Wt [lb]	Quantity	Part No	DG
5/8	1/2	0.072	5	82027	4
5/8	3/4	0.108	5	82031	4