

Heating and Cooling Solutions



4.1



Heating and Cooling Solutions

Radiant heating systems have been around since 10,000 B.C., but Viega has made them more efficient, reliable and easier to install. Viega offers a full line of prefabricated Climate Mats for wet installs, panels for dry installs, tubing, manifolds, mixing options and controls all engineered to work together. Radiant heating and cooling solutions can reduce energy costs by up to 30% for both residential and commercial buildings. Our hands-on design team can provide you with a complete design and bill of materials, so you know you have everything you need for a properly functioning system.

FEATURES AND BENEFITS

- Faster and easier than traditional radiant installation
- Typically reduces energy costs from 10-30%
- Minimizes circulation of dust, allergens and airborne contaminants
- Proven press technology helps to ensure secure connections
- Backed by a 30-year warranty on Viega Barrier PEX, PureFlow Press metal and polymer fittings
- Technical support
- Design and layout services

NOTE

Products within this section meet various codes, standards, listings and certifications. Please refer to the most up-to-date Tech Data sheets relevant to the product or to the listing agency's official record. A green dot on a Viega PureFlow Press polymer fitting indicates Smart Connect technology.

Tubing



Viega Barrier PEX tubing

- PEX
- Coil
- Oxygen diffusion barrier, protective outer layer

Technical Data

PEX designation code 5306
 Chlorine resistance ratings CL5
 UV resistance 6 months
ASTM F876, ASTM F877, ASTM F3253, NSF 61

Model 2802US

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
5/16	250	black with stripe	9.000	1	11400	4
5/16	1000	black with stripe	34.000	1	11405	4
3/8	300	black with stripe	12.900	1	11415	4
3/8	1200	black with stripe	51.600	1	11418	4
1/2	250	black with stripe	10.750	1	11428	4
1/2	300	black with stripe	17.100	1	11425	4
1/2	400	black with stripe	23.200	1	11430	4
1/2	500	black with stripe	29.000	1	11427	4
1/2	1000	black with stripe	58.000	1	11436	4
1/2	1200	black with stripe	68.400	1	11435	4
1/2	2000	black with stripe	112.000	1	11440	4
5/8	500	black with stripe	39.500	1	11445	4
5/8	1500	black with stripe	118.500	1	11450	4
3/4	150	black with stripe	16.050	1	11455	4
3/4	300	black with stripe	32.400	1	11457	4
3/4	500	black with stripe	56.500	1	11458	4
3/4	800	black with stripe	86.400	1	11460	4
3/4	1000	black with stripe	108.000	1	11462	4
1	150	black with stripe	27.000	1	11465	4
1	500	black with stripe	88.000	1	11470	4
1 1/4	100	black with stripe	27.000	1	11475	4
1 1/2	100	black with stripe	36.500	1	11480	4
2	100	black with stripe	60.300	1	11485	4

4.1



Viega Barrier PEX tubing

- PEX
- Straight length
- Oxygen diffusion barrier, protective outer layer

Technical Data

PEX designation code 5306
 Chlorine resistance ratings CL5
 UV resistance 6 months
ASTM F876, ASTM F877, ASTM F3253, NSF 61

Model 2803US

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/4	20	black with stripe	2.100	25	11500	4
1	20	black with stripe	3.500	15	11505	4
1 1/4	20	black with stripe	5.280	10	11510	4
1 1/2	20	black with stripe	7.400	5	11515	4
2	20	black with stripe	12.280	5	11520	4



Zip tie

- Plastic
- Model 2866US**

L [in]	Version	Wt [lb]	Quantity	Part No	DG
8.7	yellow	0.003	100	15304	4



U-channel fastener

- Plastic
 - Pre-drilled holes
- Model 2864US**

W [in]	L [ft]	Wt [lb]	Quantity	Part No	DG
1/2	6 1/2	1.029	16	15310	4
5/8	6 1/2	1.899	16	15311	4
3/4	6 1/2	1.300	16	15314	4