

For mounting Flexcon expansion vessels (2 - 25 litres) to a wall.  
With the Flexconsole the Flexcon vessel is set up vertically fitted to the water connection with the water nipple fitted on connection B of the console and the expansion pipe fitted to connection A.

### Technical Specifications

- Minimum/Maximum working temperature: -10 °C / 120 °C (14 °F / 248 °F).
- Minimum/Maximum working pressure: 0.2 / 10.0 bar (3 / 145 Psi).
- Suitable for addition of glycol-based anti-freeze up to 50%.
- In accordance with ANSI/ASME B1.20.1.
- Application:  
97975 and 97977 only suitable for hydronic systems.  
97976 only suitable for potable water.



### Classification General Data

|                      |                                   |
|----------------------|-----------------------------------|
| <b>Etim Group</b>    | Pressure increase/decrease        |
| <b>Etim Class</b>    | Pressure expansion vessel console |
| <b>Product Name</b>  | Flexconsole 1/2NPT x1/2NPT        |
| <b>Brand</b>         | FLAMCO                            |
| <b>Product Type</b>  | Vessel Mounting                   |
| <b>Artikelnummer</b> | 97975                             |
| <b>GTIN</b>          | 08712874979758                    |

### Attributes

|  |  |
|--|--|
| <b>Tank size</b>                         | 2 - 25 l                                       |
| <b>Built-in pressure relief valve</b>    | No   |
| <b>Thread connection central heating</b> | Internal thread cylindrical BSPP-G (ISO 228-1) |
| <b>Thread connection, tank</b>           | Internal thread cylindrical BSPP-G (ISO 228-1) |
| <b>Size of tank thread connection</b>    | 3/4 inch                                       |

### Find more information online:

Packaging data

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)