



CLEAN F9-AL

BOILER “COMBUSTION SIDE” CLEANER FOR ALUMINUM HEAT EXCHANGERS

Removes even the most stubborn combustion residue from Aluminum heat exchangers.



FEATURES and BENEFITS

- *Provides energy savings by removing combustion residue from the fire side surface of heat exchangers made from aluminum in condensing boilers*
- *Restores heat transfer to the original levels*
- *Easy two-step procedure to clean*
- *Each bottle comes with an extended spray nozzle to help with accessing the hard to reach areas in the heat exchanger*
- *Child security cap lock*
- *Security bottle seal*
- *No pouring or mixing needed*
- *Package includes two - 1L (33oz.) bottles*



© 2019 Axiom Industries Ltd.



INDUSTRIES LIMITED

DIRECTIONS:

Spray AXI-THERM CLEAN F9A directly onto the cold surface to be cleaned until the deposits to be removed are completely wet. Do not dilute prior to application. Let the product react for 10 - 20 minutes before brushing and rinsing. For aluminum heat exchangers apply AXI-THERM CLEAN F9B after the application of CLEAN F9A and subsequent rinse with plenty of water. Firing the boiler afterwards will help to further clean the heat exchanger. Thoroughly rinse the whole surface with water. In case of persistent deposits, repeat the cleaning procedure. Do not mix with other chemicals. Do not use in potable water systems. Do not ingest. Do not dispose of waste through the environment. Keep out of reach of children.

Before



After

