

Inverter Driven Heat Pump

24,000 BTU Single Zone Wall Mounted System

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

Auto Changeover
 Weekly & 24 hr. Timer
 Auto Louver: Up/Down
 Minimum Heat Mode (Wi-Fi Adapter required)
 Wireless Remote Control Included
 Auto Restart
 Economy Mode
 Energy Saving Program (ESP)
 Outdoor Unit Low Noise Schedule



MODEL NUMBERS			
Indoor Unit		ASUH24LPAS	
Outdoor Unit		AOUH24LPAS1	
System		24LPAS1	
EFFICIENCIES			
SEER		19	
SEER 2		19	
EER		9.2	
EER 2		9.2	
HSPF		11	
HSPF 2 (IV) / HSPF 2 (V)		9.8/7.6	
COP	kW/kW		3.4
COP	Btu/hW		11.6
COP2	kW/kW		3.4
COP2	Btu/hW		11.6
OUTDOOR TEMPERATURE OPERATION RANGE			
Cooling	*F(*C)	14 to 115 (-10 to 46)	
Heating		5 to 75 (-15 to 24)	
CAPACITIES			
Cooling	Rated	Btu/h	24000
	Min.—Max.		4,000—24,400
Heating	Rated		24000
	Min.—Max.		2,900—29,000
LINESET REQUIREMENTS			
Connection Method		Flare	
Liquid	in (mm)	Ø 1/4 (Ø 6.35)	
Gas		Ø 1/2 (Ø 12.7)	
Pre-charge length	ft (m)	49 (15)	
Minimum Length		16 (5)	
Max. length		66 (20)	
Max. height difference		49 (15)	
INDOOR DIMENSIONS & WEIGHT			
Net (H × W × D)	in (mm)	11 × 38-9/16 × 9-7/16 (280 × 980 × 240)	
Gross (H × W × D)		12-11/16 × 42-7/16 × 13-5/8 (322 × 1,078 × 346)	
Net Weight	lb (kg)	29 (13)	
Gross Weight		37 (17)	
OUTDOOR DIMENSIONS & WEIGHT			
Net (H × W × D)	in (mm)	24-7/8 × 31-7/16 × 11-7/16 (632 × 799 × 290)	
Gross (H × W × D)		27-1/4 × 37 × 14-3/4 (692 × 940 × 375)	
Net Weight	lb (kg)	86 (39)	
Gross Weight		95 (43)	

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ACCESSORIES

UTY-RNRUZ*	Wired remote controller
UTY-RSRY	Simple remote controller
UTY-RHRY	Simple remote controller
UTY-XWZX	External Connect Kit
UTY-XWZXZ5	External Connect Kit
UTY-XCSXZ2	External Input and Output PCB
UTY-TWRXZ2	Communication Kit
UTY-TFSXF1	Wireless LAN adapter
UTY-VMSX	Modbus Converter
UTY-TTRXZ1	24V Thermostat Converter
UTY-VTGX	Network Converter



This system combination is Energy Star qualified



+App available in Apple® App Store and Google® Play Store.

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation
<https://connect.fujitsugeneral.com>

Effective Date: 10/31/2022

Fujitsu General America, Inc. • 340 Changebridge Rd, Pine Brook, NJ 07058 • Toll Free: (888) 888-3424 • www.fujitsugeneral.com

Inverter Driven Heat Pump

24,000 BTU Single Zone Wall Mounted System

FAN DATA

Indoor Unit Airflow rate	Cooling	HIGH	CFM (m3/h)	642 (1,090)
		MED		471 (800)
		LOW		377 (640)
		QUIET		306 (520)
	Heating	HIGH		594 (1,010)
		MED		506 (860)
		LOW		377 (640)
		QUIET		306 (520)
Outdoor Unit Airflow rate	Cooling			1,560 (2,650)
	Heating			1,560 (2,650)

SOUND PRESSURE

Indoor Unit	Cooling	HIGH	dB (A)	49
		MED		42
		LOW		37
		QUIET		31
	Heating	HIGH		47
		MED		43
		LOW		37
		QUIET		32
Outdoor Unit	Cooling			53
	Heating			54

REFRIGERANT

Type	R410A		
Charge	lb oz	2 lb 16 oz	
	g	1350	
Oil Type	RB68		

ELECTRICAL SPECIFICATIONS

Voltage/Frequency/Phase		208/230 V ~60 Hz		
Available Voltage Range		187–253 V		
Current	Cooling	Rated	A	11.4
	Heating	Rated		9.1
Maximum Operating Current	Cooling			14.4
	Heating			13.9
Starting Current				11.4
MCA				17.2
Maximum Circuit Breaker				20
Input Power	Cooling	Rated	kW	2.6
		Min.–Max.		0.15–3.20
	Heating	Rated		2.07
		Min.–Max.		0.15–3.10
Power Factor	Cooling		%	99.2
	Heating			98.9


OTHER

Moisture Removal		pints/h (L/h)	6.3 (3.0)
Energy Star			Yes
Drain hose	Material		PP+HDPE
	Tip diameter	in (mm)	Ø17/32 (Ø13.8) (I.D.), Ø5/8 to 21/32 (Ø15.8 to 16.7) (O.D.)
Operation Range	Cooling	°F (°C)	64 to 90 (18 to 32)
		%RH	80 or less
	Heating	°F (°C)	86 or less (30 or less)

DIMENSIONS:

Units: In. (mm)


Wall Bracket Data:




DIMENSIONS

Units: In. (mm)

Indoor Unit



Outdoor Unit



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Airstage logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit – indoor unit).