

## Inverter Driven Heat Pump


## 12,000 BTU Slim Duct Type

Job Name \_\_\_\_\_  
 Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Submitted To \_\_\_\_\_  
 Submitted By \_\_\_\_\_  
 Reference \_\_\_\_\_

Date \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Construction \_\_\_\_\_  
 Unit No \_\_\_\_\_  
 Drawing No \_\_\_\_\_

### PRODUCT FEATURES

- Wired remote controller
- Automatic airflow adjustment
- Auto/Cool/Dry/Fan/Heat/modes
- weekly timer
- Powerful mode
- Auto changeover
- Cold prevention



### MODEL NUMBERS

Indoor Unit	ARU12RLF
Nominal Capacity	12,000

### LINESET REQUIREMENTS

Connection Method		Flare
Liquid	in (mm)	Ø1/4 (Ø6.35)
Gas		Ø3/8 (Ø9.52)
Drain hose	Material	Hard PVC
	in	Ø 3/4 (I.D.), Ø 1-1/16 (O.D.)
	mm	Ø 20.7 (I.D.), Ø 26.6 (O.D.)

### INDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	7-13/16 x 27-9/16 x 24-7/16
	mm	198 x 700 x 620
Gross (H x W x D)	in	10-13/16 x 37-3/16 x 30-3/8
	mm	274 x 945 x 772
Net Weight	lb (kg)	40 (18)
Gross Weight		51 (23)

### ELECTRICAL SPECIFICATIONS

Voltage/Frequency/Phase		208/230 V ~ 60 Hz
Voltage Range		187~264 V
Running Current	A	0.35
Input Power	W	58

### SOUND PRESSURE

Indoor Unit	Cooling	High	dB (A)	29
		Medium		28
		Low		27
		Quiet		26
	Heating	High		29
		Medium		28
		Low		27
		Quiet		24

### FAN DATA

Airflow Rate	Cooling	High	CFM (m3/h)	383 (650)
		Medium		353 (600)
		Low		324 (550)
		Quiet		283 (480)
	Heating	High		383 (650)
		Medium		353 (600)
		Low		324 (550)
		Quiet		283 (480)
Static Pressure	inWG (Pa)			0 to 0.36 (0 to 90)

### Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 30 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 30 days of installation in a residence, and installed by a Fujitsu Elite contractor

### ENCLOSURE

Enclosure	Material	Color
	Galvanized steel sheet	-

### ACCESSORIES

UTY-TTRX	3rd Party Thermostat Converter
UTD-ECS5A	Slim Duct Connector Kit
UTY-LRHUM	Wireless Remote Receiver Kit
UTY-RVNUM	Wired Remote w/backlight
UTY-RSNUM	Simple Remote
UTY-XSZX	Remote Sensor
FJ-RC-WIFI-1NA	Intesis Wired WiFi module
FJ-IR-WIFI-1NA	Intesis IR WiFi module
UTY-TFNXZ2	WiFi interface Module
UTD-GXSA-W	Auto Louver Grill Kit



ETL#: 0

Effective Date: 2/11/2020

Version ARU12RLF -2019B

Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation  
<https://portal.fujitsugeneral.com>

Fujitsu General America, Inc. • 353 Route 46 West Fairfield, NJ 07004 • Toll Free: (888) 888-3424 • [www.fujitsugeneral.com](http://www.fujitsugeneral.com)

Inverter Driven Heat Pump

12,000 BTU Slim Duct Type

DIMENSIONS

Units: In. (mm)

