

Feature

- 125# WSP / 200# WOG
- Lead free brass body
- FNPT x FNPT
- Threaded ends (ASME B1.20.1-NPT)
- Screw in bonnet
- Non-rising stem
- Solid wedge disc
- AB1953, NSF/ANSI 61 & 372 certified




Meet BAA requirement



Pressure/ Temperature rating	
200 psi from 32 °F to 160 °F	125 psi max. at 344 °F

Material

	Part	Material	Specification
1	Body	Lead Free Brass	ASTM B927 C28500
2	Wedge	Lead Free Brass	ASTM B927 C28500
3	Bonnet	Lead Free Brass	ASTM B927 C28500
4	Stem	Lead Free Brass	ASTM B927 C28500
5	Ring	Lead Free Brass	ASTM B927 C28500
6	Packing ring	Graphite	WRAS approved
7	Packing nut	Brass	ASTM B124 C37700
8	Handwheel	Aluminum	B85
9	Disk	Aluminum	B85
10	Nut	Steel / Zc plated	A36



Dimension, Cv, Weight

Size	T	A [in]	C [in]	H [in]	L [in]	P [in]	Cv	Wt. [lb]
1/2"	1/2 - 14 NPT	1.97	0.65	2.79	2.36	0.51	12.4	0.54
3/4"	3/4 - 14 NPT	2.12	0.65	3.17	2.36	0.74	27.7	0.80
1"	1 - 11.5 NPT	2.44	0.78	3.93	2.75	1.00	56.8	1.18
1 1/4"	1 1/4 - 11.5 NPT	2.75	0.86	4.21	3.15	1.25	90.7	1.80
1 1/2"	1 1/2 - 11.5 NPT	2.84	0.86	4.82	3.15	1.50	137	2.40
2"	2 - 11.5 NPT	3.23	0.96	6.27	3.75	2.00	304	3.96
2 1/2"	2 1/2 - 8 NPT	3.81	1.10	70.9	5.12	2.36	340	6.80
3"	3 - 8 NPT	4.37	1.29	8.03	5.12	2.79	413	8.66
4"	4 - 8 NPT	5.15	1.49	10.31	5.90	3.81	725	15.52

