

Lead Free Brass In-Line Check Valve

Feature

200# WOG Lead free brass body FNPT x FNPT Threaded ends (ASME B1.20.1-NPT) Spring loaded Horizontal or vertical installation NBR soft seat AB1953, NSF/ANSI 61 & 372 certified





Pressure/ Temperature rating 200 psi from 15 °F to 200 °F

Material

	Part	Material	Specification	
1	Body	Lead Free Brass	ASTM B927 C27450	
2	End piece	Lead Free Brass	ASTM B927 C27450	
3	Stem	POM	NSF Approved	
4	Seat	NBR	NSF Approved	
5	Disk	POM	NSF Approved	
6	Spring	Stainless Steel	AISI 304 S30400	



Dimension, Cv, Weight

redwhitevalvecorp.com

Size	ФА	н	Cv	Wt.
	[in]	[in]		[lb]
1⁄2"	1.18	1.89	3.33	0.24
3/4"	1.46	2.09	6.05	0.34
1"	1.77	2.32	9.88	0.52
1 ¼"	2.20	2.64	15.9	0.76
1 ½"	2.48	2.76	22.0	1.04
2"	3.11	3.15	38.1	1.60



MARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www. P65Warnings.ca.gov.

pg1/1 [181130]

Dravings, photos and data are provided for information only and subject to change without notice. No part of this document may be reproduced, or poind, modified or adapted, without the prior written consent of the copyright owner, unless otherwise indicated. The Drinking Water Act has defined lead free as having the average wetted surface ratio of the fixture to contain less than .25% of lead per volume.