

SHC Mini-Tanks

Technical specifications

Model	SHC 2.5	SHC 4	SHC 6
Item number	233219	234046	235089
Phase - 60/50 Hz	single		
Voltage	120 V		
Wattage	1300 W		
Amperage	11.3 A		
Electrical connection	Plugs into 120 V receptacle with supplied cord (43" long)		
Water connections	brass 1/2" NPT		
Nominal water volume	2.65 gal (10 l)	4.0 gal (15 l)	6.0 gal (22.7 l)
Weight empty	15.9 lb (7.2 kg)	19.8 lb (9.0 kg)	26.5 lb (12.0 kg)
Weight full	38.6 lb (17.5 kg)	52.9 lb (24.0 kg)	76.3 lb (34.6 kg)
Height (includes P&T valve)	18 11/16" (475 mm)	19 3/4" (501 mm)	20 1/2" (520 mm)
Width	11" (280 mm)	12 5/8" (320 mm)	15 1/8" (385 mm)
Depth	10 5/8" (270 mm)	12 1/2" (318 mm)	15" (380 mm)
Maximum operating pressure	150 psi (10 bar)		
Adjustable temperature range	86 °F - 140 °F (30 °C - 60 °C)		
Recovery time	18 minutes	27 minutes	45 minutes
Standby energy loss @ 131 °F (55 °C)	0.37 kWh/day	0.39 kWh/day	0.43 kWh/day



Certified to ANSI/UL Std. 174
Conforms to CAN/CSA Std. 22.2 No. 110



Tested and certified by WQA against
NSF/ANSI/CAN 372 for lead free compliance

ISO 9001
CERTIFIED