



## Features & Benefits

### The 0015e3® ECM circulator: Three settings. One reputation.



Use the Cast Iron 0015e3 with a Taco Switching Relay or Zone Valve Control



Use the Stainless Steel 0015e3 for open loop potable hot water systems with up to 1,000 feet of recirculation piping

- 18' Shut-off head, 16 gpm max flow
- Replaces all 3-speed hydronic circulators in its class
- High-efficiency ECM motor uses up to 85% less electricity
- **SureStart®** automatic unblocking and air purging mode
- **BIO Barrier®** protects pump from system contaminants (Cast Iron only)
- **Green Mode** active system monitoring and automatic power optimization
- Nut-grabber feature on flanges for easier fit-up
- Dual electrical knockouts, 6" stranded wire leads included for easy wiring
- Integral Flow Check (IFC®) included
- Double insulated — No ground wire required
- Whisper quiet operation
- Cast Iron models available with standard or universal flange
- Stainless Steel models available with universal flange or 1" union connection
  - Customizable 1/2" & 3/4" union fitting sets available in sweat, NPT or press (Sold Separately)

#### Multi-color LED showing operating mode and error code diagnostics



**Orange LED:**  
Indicates 007e is running normally



**SureStart® LED:**  
Indicates the innovative **SureStart®** automatic unblocking and air purge is active



**Green Mode LED:**  
Indicates the 007e is running in **Green Mode** for power optimization

#### Replaces ALL 3-speed hydronic circulators in its class

Taco	Grundfos	Armstrong	Xylem/B&G	Wilco
005	UP15-10	Astro 225	ecocirc 19-16	Star S 16
006	UP15-42	Astro 230	NBF-22/NRF-22	Star S 21
007	UPS15-55	Astro 250	NBF-25/NRF-25	Stratos ECO 16
008	UPS15-58	Astro 20	NBF-9/NRF-9F/LW	
0015	Alpha 15-55	Astro 25	SSF-9U/LW	
0015 3-Speed	Alpha2 15-55	Astro 30		
007e		Astro 30-3		
		Astro 50-3		
		Compass H20-20		



