

# The stometric state of the store of the stor



# **Firestop Sealant**

- Penetrations & joint applications
- Flexible cure
- 3-year shelf life
- Non-sag
- Caulk grade

W-RATING TESTED LEVEL OF PROTECTION FROM WATER INTRUSION

33 UL systems passed the water leakage test to obtain Class 1 W-rating

## We draw the line at fire & smoke penetration.



### For more information visit metacaulk.com/mc150



FILL VOID OR CAVITY MATERIALS FOR USE IN THROUGH-PROFERATION FIRSTOP SYSTEMS. SEE UIL FIRE RESISTANCE URRECTORY 12/2 Sound Transmission Class of BU Sound Transmission Loss of BU

TESTED TO ASTM E814 (UL 1479) ASTM E1966 (UL 2079) Sound Transmission Class (**STC) 65** - The test was performed in accordance with ASTM E 90-09, Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions.

SUBJECT TO THE CONDITIONS OF APPROVAL AS A WALL AND FLOOR PENETRATION FIRE STOP WHEN INSTALLED AS DESCRIBED IN THE CURRENT EDITION OF THE FM APPROVAL GUIDE.





### RectorSeal, LLC 2601 Spenwick Drive - Houston, TX 77055 800-231-3345 metacaulk.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50580-1119