PRODUCT DATA SHEET



A CSW Industrials Company

COIL-RITE™ Evaporator Coil Cleaner

Description

In just minutes, non-acid COIL-RITE removes grime, oil, grease and dust from air conditioning coils, air handling equipment, as well as electronic and permanent air filters and all mechanical equipment. Powerful surfactant chemicals actually lift grease and dirt off normally inaccessible surfaces. A COIL-RITE cleaning reduces head pressure on over-heated compressors, avoids premature equipment breakdown, increases equipment efficiency and decreases power consumption and costs. It is safe for all metals, including aluminum, when used as directed.

Instructions

Read SDS, all directions, hazard and precautionary statements before using this product.

DIRECTIONS FOR USE:

1. Appropriately dilute with water as needed and detailed below.

For extremely dirty coils & equipment -

1 part COIL-RITE to 4 parts water.

For all types of filters -

1 part COIL-RITE to 5 parts water.

For continuous maintenance -

1 part COIL-RITE to 5-10 parts water.

2. Shut off system. **3.** Apply the diluted solution with a trigger sprayer, hand powered tank or high pressure washer. Use a brush to help faster penetration of hard encrusted dirt. **4.** Allow 5 to 10 minutes soaking time before rinsing. On an operating evaporator coil, rinsing is not required since the condensate will flush out all the loosened slime and dirt. **5.** Rinsing the evaporator coil is not necessary if the unit will be turned on soon after cleaning, but a thorough rinsing with low-pressure water will ensure optimum results.

Applications

Coil-Rite can be safely used on aluminum, copper, stainless steel and painted surfaces. It is formulated to clean metal coils, fiber or metal mesh filters, and other metal surfaces where acids should not be used.



Characteristics | Features

- · Cleans grime, oil, grease and dust
- · Non-acid, Non-flammable
- · Can be used indoors and outdoors
- Will not harm copper or aluminum
- · Biodegradable*
- Low foam

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
82612	Gallon (3.8L)	4	36	1.27

^{*} Contains the best available biodegradable surfactants and detergents.



Specifications

Wt/Gal @ 77° F 10.0 lbs./gal.

Flash Point SETA CC None

Color Green

Shelf Life 2 years



Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty



For more information on our product limited warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC