

# **Submittal Data Information**

101-081

## Low Water Cutoff

**Effective**: April 18, 2022 **Supersedes**: 10/01/17

Job: Engi	neer:	Contractor:	Rep:
ITEM NO.	MODEL NO.		

### Listings/Approvals

UL GUIDE (MBPR) for Limit Controls per UL Standard 353 Limit Controls UL GUIDE (MBPR7) Controls, Limit Certified for Canada CSA Standard C22.2 UL GUIDE (MCUR2) for Electrode Assemblies – Component (remote probes) FM Approved (LF only)

Fully compliant with CSD-1 requirements

#### **Material of Construction**

LTA-2 and LF Control Unit: NEMA Type 1(For indoor use only). Formed sheet metal with powder coat/plated finish enclosure, knock-outs for 1/2" conduit fittings.

LTR Unit: UL 94 V0 rated engineered plastic enclosure

Remote Probe: NEMA Type 4. Drawn sheet metal with powder coat/plated finish enclosure. Opening for 1/2" conduit fitting.


All models are not for use in hazardous locations

#### **Performance Data**


Category	LF Model	LTA-2 Model	LTR Model
Maximum Pressures Steam	250 psi (17.6 kg/cm²)	NA	N/A
Maximum Pressures Hot Water	250 psi (17.6 kg/cm²) @250°F (121°C)	250 psi (17.6 kg/cm²) @250°F (121°C)	160 psi (11.2 kg/cm²) @ 250°F (121°C)
Maximum Ambient Temp.	150°F (66°C)	150°F (66°C)	120°F (49°C)
Delays	Automatic	N/A	N/A
Probe Sensitivity	20K Ohms, extended operation to 40K Ohms	20K Ohms, extended operation to 40K Ohms	20K Ohms, extended operation to 40K Ohms
Control Power Consumption	3VA @ 120VAC, 3VA @ 24VAC	2.8VA @ 120VAC, 2.8VA @ 24VAC	1.5VA @ 24VAC
Input Supply Voltage	120VAC, 24VAC*	120VAC, 24VAC*	24VAC*

<sup>\*24</sup>VAC supplied by a Class 2 power source


#### **Model LF Dimensions**



#### **Model LTA-2 Dimensions**



#### **Model LTR Dimensions**



#### **Remote Probe Dimensions**

