

# Loop- & J-Hangers



Loop- & J-Hangers

# Loop- & J-Hangers

## 115 STANDARD DUTY LOOP HANGER

- Flared edges help prevent any sharp surfaces from coming into contact with the pipe (1/2" to 4" sizes)
- Retained insert nut helps ensure the loop hanger and insert nut stay together
- Recommended for the suspension of stationary non-insulated pipe lines
- Manufactured to use the minimum rod size permitted by NFPA® for fire sprinkler piping
- Conforms with Federal Specification WW-H-171 (Type 10), Manufacturers Standardization Society (MSS) SP-58 (Type 10)



Material: Steel  
Finish: Pregalvanized



Part Number	Description	F ↓	Certifications
1150050EG	1/2" Pipe, 0.84" OD, 3/8" Rod	300 lb	cULus
1150075EG	3/4" Pipe, 1.05" OD, 3/8" Rod	300 lb	cULus, FM
1150100EG	1" Pipe, 1.315" OD, 3/8" Rod	300 lb	cULus, FM
1150125EG	1 1/4" Pipe, 1.66" OD, 3/8" Rod	300 lb	cULus, FM
1150150EG	1 1/2" Pipe, 1.9" OD, 3/8" Rod	300 lb	cULus, FM
1150200EG	2" Pipe, 2.375" OD, 3/8" Rod	300 lb	cULus, FM
1150250EG	2 1/2" Pipe, 2.875" OD, 3/8" Rod	525 lb	cULus, FM
1150300EG	3" Pipe, 3.5" OD, 3/8" Rod	525 lb	cULus, FM
1150350EG	3 1/2" Pipe, 4" OD, 3/8" Rod	585 lb	cULus, FM
1150400EG	4" Pipe, 4.5" OD, 3/8" Rod	650 lb	cULus, FM
1150500EG	5" Pipe, 5.563" OD, 1/2" Rod	1,000 lb	cULus, FM
1150600EG	6" Pipe, 6.625" OD, 1/2" Rod	1,000 lb	cULus, FM
1150800EG	8" Pipe, 8.625" OD, 1/2" Rod	1,000 lb	cULus, FM