

Riser Clamps

510 EZ RISER

- Recommended for suspending vertical steel pipe risers
- Slotted holes make assembly easy, eliminating loose hardware
- Serrated flange-head bolts eliminate need for wrenches on both bolt and nut
- Conforms with Federal Specification WW-H-171 (Type 8), Manufacturers Standardization Society (MSS) SP-58 (Type 8)



**Patent No.: 8,276,854
8,573,543**



Part Number	Description	F ↓	Certifications
Material: Stainless Steel 304			
510050S4	S304, 1/2" Pipe, 0.84" OD	255 lb	—
510075S4	S304, 3/4" Pipe, 1.05" OD	255 lb	—
5100100S4	S304, 1" Pipe, 1.315" OD	255 lb	—
5100125S4	S304, 1 1/4" Pipe, 1.66" OD	255 lb	—
5100150S4	S304, 1 1/2" Pipe, 1.9" OD	255 lb	—
5100200S4	S304, 2" Pipe, 2.375" OD	255 lb	—
5100250S4	S304, 2 1/2" Pipe, 2.875" OD	390 lb	—
5100300S4	S304, 3" Pipe, 3.5" OD	530 lb	—
5100400S4	S304, 4" Pipe, 4.5" OD	810 lb	—
5100500S4	S304, 5" Pipe, 5.563" OD	1,160 lb	—
5100600S4	S304, 6" Pipe, 6.625" OD	1,570 lb	—
5100800S4	S304, 8" Pipe, 8.625" OD	2,500 lb	—
5101000S4	S304, 10" Pipe, 10.75" OD	2,500 lb	—
Material: Steel — Finish: Electrogalvanized			
510050EG	EG, 1/2" Pipe, 0.84" OD	255 lb	—
510075EG	EG, 3/4" Pipe, 1.05" OD	255 lb	—
5100100EG	EG, 1" Pipe, 1.315" OD	255 lb	—
5100125EG	EG, 1 1/4" Pipe, 1.66" OD	255 lb	—
5100150EG	EG, 1 1/2" Pipe, 1.9" OD	255 lb	—
5100200EG	EG, 2" Pipe, 2.375" OD	255 lb	cULus
5100250EG	EG, 2 1/2" Pipe, 2.875" OD	390 lb	cULus
5100300EG	EG, 3" Pipe, 3.5" OD	530 lb	cULus
5100350EG	EG, 3 1/2" Pipe, 4" OD	670 lb	cULus
5100400EG	EG, 4" Pipe, 4.5" OD	810 lb	cULus
5100500EG	EG, 5" Pipe, 5.563" OD	1,160 lb	cULus
5100600EG	EG, 6" Pipe, 6.625" OD	1,570 lb	cULus
5100800EG	EG, 8" Pipe, 8.625" OD	2,500 lb	cULus
5101000EG	EG, 10" Pipe, 10.75" OD	2,500 lb	—
5101200EG	EG, 12" Pipe, 12.75" OD	2,700 lb	—
5101400EG	EG, 14" Pipe, 14" OD	2,700 lb	—
5101600EG	EG, 16" Pipe, 16" OD	2,900 lb	—