



Telescoping Pipe Stand – CTS04



- Supports and fastens low to the ground horizontal pipe runs
- Complete out-of-the-box assembly provides a compact solution, simplifying material handling and reducing the amount of storage space required
- Designed to minimize fabrication and reduce the installation time of a complete stand by up to 80%
- Telescoping post provides fast vertical height adjustment
- V-bolt fastener accommodates multiple pipe sizes, reducing inventory by over 65%
- Easy "push-to-install" nVent CADDY Rod Lock feature allows the V-bolt to assemble quickly
- Integrated weep hole at bottom of stand provides drainage for condensation
- Includes four holes for anchoring base to floor
- Conforms with Federal Specification WW-H-171 (Type 37, 38), Manufacturers Standardization Society ANSI®/MSS-SP-58 (Type 37)



Part Number	CTS04
Material	Steel
Finish	Electrogalvanized
Static Load Safety Factor	3.5:1
Pipe Size	1" – 8"
A	20" – 40 1/2"
B	6 1/2"
C	6 1/2"
D	5"
Hole Size (HS)	9/16"
Static Load (F)	1,370 lb
Standard Packaging Quantity	1 pc
UPC	78285695311

Part Number	Pipe Size	A
CTS04	1"	20" - 36 1/4"
	1 1/4"	20 1/4" - 36 1/2"
	1 1/2"	20 3/8" - 36 5/8"
	2"	20 5/8" - 36 7/8"
	3"	21 1/4" - 37 1/2"
	4"	21 7/8" - 38 1/8"
	5"	22 1/2" - 38 3/4"
	6"	23 1/8" - 39 1/4"
	8"	24 1/4" - 40 1/2"
CTS10	5"	23" - 39 1/4"
	6"	23 1/2" - 40"
	8"	24 3/4" - 41"
	10"	26" - 42 1/4"
	12"	27 1/4" - 43 3/8"
	14"	27 7/8" - 44 1/8"
	16"	29 1/8" - 45 1/4"
	18"	30 1/4" - 46 3/8"
	20"	31 3/8" - 47 1/2"
	24"	33 5/8" - 49 7/8"

When insulating pipe install V-bolt after insulation.

Telescoping pipe stand can accommodate pipes up to 24" when v-bolt is removed. Installer must determine weight of the pipe and proper spacing when supporting larger sizes.

Installer must determine weight of the pipe and proper spacing when supporting larger sizes.

ANSI is a registered trademark of American National Standards Institute.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

