

Clevis Hangers

401 CLEVIS HANGER

- Recommended for the suspension of stationary non-insulated pipe lines
- Also commonly used for the suspension of insulated pipe lines
- Flared edges help prevent sharp surfaces from coming into contact with the pipe (1/2" to 2" pipe sizes)
- Clevis bottom pivots to allow pipe to be fed from either direction
- Conforms with U.S. Federal Specification WW-H-171 (Type 1), Manufacturers Standardization Society (MSS) SP-58 (Type 1)



Material: Steel



Part Number	Description	F ↓	Certifications
Finish: Electrogalvanized; Pregalvanized			
4010050EG	EG, PG, 1/2" Pipe, 0.84" OD, 3/8" Rod	610 lb	cULus
4010075EG	EG, PG, 3/4" Pipe, 1.05" OD, 3/8" Rod	610 lb	cULus, FM
4010100EG	EG, PG, 1" Pipe, 1.315" OD, 3/8" Rod	610 lb	cULus, FM
4010125EG	EG, PG, 1 1/4" Pipe, 1.66" OD, 3/8" Rod	610 lb	cULus, FM
4010150EG	EG, PG, 1 1/2" Pipe, 1.9" OD, 3/8" Rod	610 lb	cULus, FM
4010200EG	EG, PG, 2" Pipe, 2.375" OD, 3/8" Rod	610 lb	cULus, FM
4010250EG	EG, PG, 2 1/2" Pipe, 2.875" OD, 1/2" Rod	1,130 lb	cULus, FM
4010300EG	EG, PG, 3" Pipe, 3.5" OD, 1/2" Rod	1,130 lb	cULus, FM
4010350EG	EG, PG, 3 1/2" Pipe, 4" OD, 1/2" Rod	1,130 lb	cULus, FM
4010400EG	EG, PG, 4" Pipe, 4.5" OD, 5/8" Rod	1,130 lb	cULus, FM
4010500EG	EG, PG, 5" Pipe, 5.563" OD, 5/8" Rod	1,430 lb	cULus, FM
4010600EG	EG, PG, 6" Pipe, 6.625" OD, 3/4" Rod	1,940 lb	cULus, FM
4010800EG	EG, PG, 8" Pipe, 8.625" OD, 3/4" Rod	2,000 lb	cULus, FM
4011000EG	EG, PG, 10" Pipe, 10.75" OD, 7/8" Rod	3,600 lb	—
4011200EG	EG, PG, 12" Pipe, 12.75" OD, 7/8" Rod	3,800 lb	—
4011400EG	EG, PG, 14" Pipe, 14" OD, 1" Rod	4,200 lb	—
4011600EG	EG, PG, 16" Pipe, 16" OD, 1" Rod	4,600 lb	—
4011800EG	EG, PG, 18" Pipe, 18" OD, 1 1/8" Rod	4,800 lb	—
4012000EG	EG, PG, 20" Pipe, 20" OD, 1 1/4" Rod	4,800 lb	—
4012400EG	EG, PG, 24" Pipe, 24" OD, 1 1/4" Rod	4,800 lb	—
Finish: Hot-Dip Galvanized			
4010050HD	HD, 1/2" Pipe, 0.84" OD, 3/8" Rod	610 lb	cULus
4010075HD	HD, 3/4" Pipe, 1.05" OD, 3/8" Rod	610 lb	cULus, FM
4010100HD	HD, 1" Pipe, 1.315" OD, 3/8" Rod	610 lb	cULus, FM
4010125HD	HD, 1 1/4" Pipe, 1.66" OD, 3/8" Rod	610 lb	cULus, FM

A shield is recommended for insulated pipe applications to effectively distribute the load.