



# Loop- & J-Hangers

## 103 LOOP HANGER WITH INSULATION SHIELD

- Recommended for the suspension of stationary insulated piping
- Protection shield is welded to loop before plating



Material: Steel  
Finish: Pregalvanized; Electrogalvanized

Part Number	Description	
1030150EG	1 1/2" Shield, 1.9" OD, 3/8" Rod	300 lb
1030200EG	2" Shield, 2.37" OD, 3/8" Rod	300 lb
1030250EG	2 1/2" Shield, 3.12" OD, 1/2" Rod	1,000 lb
1030300EG	3" Shield, 3.62" OD, 1/2" Rod	1,000 lb
1030350EG	3 1/2" Shield, 4" OD, 1/2" Rod	1,000 lb
1030400EG	4" Shield, 4.5" OD, 5/8" Rod	1,100 lb
1030500EG	5" Shield, 5.56" OD, 5/8" Rod	1,100 lb
1030600EG	6" Shield, 6.62" OD, 3/4" Rod	1,250 lb

Flared edges on sizes through 4" only. For sizes larger than 6" see Model 403 Clevis Hanger.

## 104 LOOP HANGER FOR PLASTIC PIPE

- Recommended for the suspension of stationary flexible EPDM or Polypropylene plastic piping
- Use hanger with V-trough (model VTR) for continuous support of flexible or hot piping services



Material: Steel  
Finish: Electrogalvanized

Part Number	Description	
1040100EG	1/2"-2" Pipe, 3/8" Rod	175 lb
1040200EG	2 1/2"-4" Pipe, 1/2" Rod	175 lb