

NVENT CADDY SUPERFIX 454 STANDARD DUTY, 1.26"-1.378" OD, 1" PIPE, 1 1/4" COPPER TUBE

CATALOG NUMBER

454006



FEATURES

Recommended for the suspension of stationary non-insulated pipe lines Easy-to-close clamp for steel pipe and copper tube Unique hinged design eliminates the need to disassemble the clamp prior to installation Clamp can be closed with one hand, without ever turning a screw All-steel design of the closing mechanism retains strength even when exposed to heat Comes with a welded 3/8" cap nut, allowing easy attachment to threaded rod

Combo head bolt works with slotted, hex, or Phillips drivers

Conforms with Manufacturers Standardization Society (MSS) SP-58 (Type 12)

Category II noise reduction according to DIN EN ISO 3822-1

Compliant for sound insulation design according to DIN 4109

Reaction-to-fire classification is "E" in compliance with DIN EN 13501-1

PRODUCT ATTRIBUTES

Material: Steel;EPDM-SBR Rubber Finish: Electrogalvanized Temperature: -58 to 230 °F Outer Diameter: 1.260" – 1.378" Pipe Size: 1" Copper Tube Size: 1 1/4"

Rod Size: 3/8"


B: 29/32"

Static Load: 180 lb

ADDITIONAL PRODUCT DETAILS

Lining is EPDM rubber.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support Europe

Netherlands: +31 800-0200135 France: +33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

NVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

their respective owners. nVent reserves the right to change specifications without notice. 2