

## nVent CADDY Rod Lock Plywood Form Preset Anchor – CRLW50EG





- Eliminate overhead drilling into building structure nVent CADDY Rod Lock Preset Anchors are cast in place
- Nails hold the anchor in place during the pour and easily break off with a strike of a hammer once the plywood forms are removed
- Easy "push-to-install" design allows installers to simply push the threaded rod through the mounting hole, instantly holding it in position
- Works with slightly damaged threads and minor burrs on the threaded rod
- Prefabricated assemblies easily lift and lock into place, helping to save time and money
- Plastic flange acts as insert locator when the forms are removed
- Rated for cracked concrete per ICC-ES AC446 according to ICC-ES ESR-3864 evaluation report
- Suitable for seismic bracing according to ICC-ES ESR-3864 evaluation report









| Part Number                 | CRLW50EG                       |
|-----------------------------|--------------------------------|
| Material                    | Steel                          |
| Finish                      | Electrogalvanized              |
| Rod Size (RS)               | 1/2"                           |
| Diameter (Ø)                | 1.9"                           |
| Height 1 (H1)               | 3.3"                           |
| Height 2 (H2)               | 2 1/2"                         |
| Static Load (F)             | 1,618 lb                       |
| Certifications              | cULus<br>FM<br>ICC-ES ESR-3864 |
| Standard Packaging Quantity | 25 рс                          |
| UPC                         | 78285679385                    |



FM is a registered certification mark of FM Approvals LLC, LTD. ICC-ES is a registered trademark of ICC Evaluation Service, LLC. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

New tproducts shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

