

## DULUX PRE-PAINT SUGAR SOAP POWDER

### TECHNICAL DATA SHEET

Version 2 – 2018 SEPTEMBER

THIS ISSUE SUPERSEDES ALL PREVIOUS PUBLICATIONS

### PRODUCT DESCRIPTION

Used to clean and degrease surfaces prior to repainting – the key to a great paint finish.

### PRODUCT USES

---

- Used to clean and degrease surfaces prior to repainting. One of the main reasons for paint flaking on interior surfaces is the lack of adhesion resulting from repainting over a thin layer of surface contaminant such as dirt and vaporised cooking oil.
- **Dulux Pre-Paint Sugar Soap** is also used to remove obstinate grime, even when repainting has not been considered.
- Can also be used to clean baths, basins, tiles etc.

### FEATURES AND BENEFITS

---

- Ideal for cleaning walls and preparing them for painting.
- Concentrated – less needed for maximum effectiveness.
- Quick and easy to use, low foaming, non-caustic and non-abrasive.
- General purpose cleaner – removes all kinds of household dirt.

### PRODUCT INFORMATION

---

<b>Physical State</b>	White Sugar-like crystals
<b>Flash Point</b>	Non flash
<b>Water Miscibility</b>	Yes

## DULUX PRE-PAINT SUGAR SOAP POWDER

### APPLICATION INFORMATION

---

Reaction Time	15 to 30 minutes to dissolve most grime.
Thinner	None required except water to dissolve crystals.
Substrates	Plaster cement, concrete, bricks, ceramic, metal, painted surfaces (water based or solvent based) or surfaces requiring degreasing.
Precautions:	<p>Always protect linoleum, parquet, carpets, fabric and polished surfaces from contact with <b>Dulux Pre-Paint Sugar Soap</b> solutions. Drop Sheets are the best way to protect such surfaces.</p> <p>Will not remove lacquer, adhesives, bitumen or deeply penetrated oil and grease – use <b>Dulux Pre-Paint Brush Cleaner/Degreaser</b> for such purposes.</p> <p><b>Dulux Pre-Paint Sugar Soap</b> solutions should not be used on aluminium or wooden surfaces.</p>
Process Details	<p>Dissolve one tablespoons of <b>Dulux Pre-Paint Sugar Soap</b> in 1 litre of warm water. Wearing plastic or rubber gloves, and using a cloth, brush or sponge, wash the surface by starting at the bottom, and working upwards. When the grime is softened thoroughly (15min to 30min), rinse the entire surface with clean water. For general cleaning of walls and ceilings, use at half strength (one tablespoon to 1 litre warm water).</p> <p>To remove stubborn dirt from baths, basins and tiles, sprinkle a little <b>Dulux Pre-Paint Sugar Soap</b> into the bath or onto a cloth and rub down. Rinse thoroughly with clean water.</p>

### HEALTH AND SAFETY INFORMATION

---

**WARNING!** Sugar Soap looks like sugar - store it in a cool safe place out of reach of children.

This product contains no added lead. Avoid contact with skin or eyes. If accidentally swallowed, seek medical advice immediately and show this container to the doctor. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes.

If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. As **Dulux Pre-Paint Sugar Soap** is an extremely strong alkaline detergent, always wear gloves and goggles when working with it.

Do not empty into drains or watercourses. To avoid the risk of spillage, always store and transport containers in a secure upright position. Refer to Material Safety Data Sheet for complete information.

## DULUX PRE-PAINT SUGAR SOAP POWDER

### ADDITIONAL INFORMATION

---

Packaging	500g
Storage Conditions	Store under cool dry conditions away from direct sunlight, heat and extreme cold.
Disclaimers	N/A product specific

### TDS STANDARD DISCLAIMER

---

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond Dulux control.

Important Note; Technology may change with time, necessitating changes to this Technical Data Sheet (TDS).

It is the responsibility of the user to ensure that the latest TDS is being used for reference. Dulux Technical Data Sheets are available on our website [www.duluxtrade.co.za](http://www.duluxtrade.co.za) or please contact: Dulux On-Line on 0860 330 111. Email [ZA.Helpline@akzonobel.com](mailto:ZA.Helpline@akzonobel.com)

ICI Dulux (Pty) Ltd is part of AkzoNobel. ICI Dulux (Pty) Ltd Reg No.1946/020769/07