AkzoNobel



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

WOODGARD EXT TIMBAPRE

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GHS product identifier : \(\sumsymbol{V}\) WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Vuse in accordance with directions on the can.

1.3. Details of the supplier of the safety data sheet

ICI DULUX (PTY) LTD NO. 1 PAINTS PLACE DICKENS ROAD UMBOGINTWINI

4126

SOUTH AFRICA

e-mail address of person

responsible for this SDS

: ZA.Helpline@akzonobel.com

1.4 Emergency telephone number

<u>Supplier</u>

Telephone number : Customer Care 0860 330 111 (Available week days from 08:00 to 16:30)

Emergency details: after hours: refer to website for MSDS

Version : 3

Date of previous issue : 15-12-2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Fam. Liq. 3, H226 Carc. 1B, H350 Repr. 1B, H360D STOT SE 3, H336 STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

${f 7}$ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 2: Hazards identification

Hazard pictograms









Signal word : Danger

Hazard statements : ▶226 - Flammable liquid and vapor.

H336 - May cause drowsiness or dizziness.

H350 - May cause cancer.

H360D - May damage the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

General: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention: P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

or hearing protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P260 - Do not breathe vapor.

Response : P391 - Collect spillage.

P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage : P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Keep cool.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

Hazardous ingredients: Maphtha (petroleum), hydrodesulfurized heavy

Solvent naphtha (petroleum), medium aliph.

calcium bis(2-ethylhexanoate)

Methyl ethyl ketoxime

Supplemental label

elements

: Contains neodecanoic acid, cobalt salt and butanone oxime. May produce an

allergic reaction.

Annex XVII - Restrictions

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and : Restricted to professional users.

articles

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Yes, applicable.

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 2/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 2: Hazards identification

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Туре |
|--|--|-----------|--|---|---------|
| Naphtha (petroleum), hydrodesulfurized heavy | EC: 265-185-4 CAS: 64742-82-1 | ≥20 - ≤25 | Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 2, H373 (respiratory system) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 | - | [1] |
| Solvent naphtha (petroleum) medium aliph | EC: 265-191-7 CAS: 64742-88-7 Index: 649-405-00-X | ≤10 | Asp. Tox. 1, H304 | - | [1] |
| Solvent naphtha (petroleum), medium aliph. | EC: 265-191-7 CAS: 64742-88-7 Index: 649-405-00-X | <10 | STOT RE 1, H372 (central nervous system (CNS)) Asp. Tox. 1, H304 | - | [1] |
| Solvent naphtha (petroleum), heavy arom. | EC: 265-198-5 CAS: 64742-94-5 Index: 649-424-00-3 | ≤5 | STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 | - | [1] |
| Solvent naphtha (petroleum), light arom. | REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 Index: self classified | ≤3 | Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 | - | [1] |
| Reaction Mass of Ethylbenzene and M- Xylene and P-Xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 | ≤3 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 | ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 6670 ppm | [1] [2] |
| Solvent naphtha (petroleum), light arom. | REACH #: 01-2119455851-35 EC: 265-199-0 CAS: 64742-95-6 | ≤3 | Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066 | - | [1] |
| calcium bis | REACH #: | <1 | Eye Dam. 1, H318 | - | [1] |

Date of issue/Date of revision : 7-6-2023 Date of previous issue :15-12-2022 Version : 3 3/23

▼ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 3: Composition/information on ingredients

| • | | | 9 | | |
|-------------------------------|--|------|---|---|---------|
| (2-ethylhexanoate) | 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6 | | Repr. 1B, H360D | | |
| neodecanoic acid, cobalt salt | EC: 248-373-0 CAS: 27253-31-2 | <1 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Chronic 3, H412 | ATE [Oral] = 500 mg/kg | [1] |
| Methyl ethyl ketoxime | REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0 | ≤0.3 | Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 STOT SE 1, H370 (upper respiratory tract) STOT SE 3, H336 STOT RE 2, H373 (blood system) | ATE [Oral] = 100 mg/kg ATE [Dermal] = 1100 mg/kg | [1] |
| Mesitylene | EC: 203-604-4 CAS: 108-67-8 Index: 601-025-00-5 | ≤0.3 | Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above. | STOT SE 3, H335: C ≥ 25% | [1] [2] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 4/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 4: First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains neodecanoic acid, cobalt salt, butanone oxime. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Date of issue/Date of revision : 7-6-2023 Date of previous issue :15-12-2022 Version : 3 5/23

✓ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version : 3 6/23 Date of previous issue

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 6: Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

• Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

| | Notification and MAPP threshold | Safety report threshold |
|-----|---------------------------------|-------------------------|
| P5c | 5000 tonne | 50000 tonne |
| E2 | 200 tonne | 500 tonne |

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 7/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|--|
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes. |
| Mesitylene | EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 100 mg/m³ 8 hours. |

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|------------------------------------|------|------------------|------------------------|------------|----------|
| ₩aphtha (petroleum), | DNEL | Long term | 0.41 mg/m ³ | General | Systemic |
| hydrodesulfurized heavy | | Inhalation | | population | |
| | DNEL | Long term | 1.9 mg/m ³ | Workers | Systemic |
| | | Inhalation | | | |
| | DNEL | Long term | 178.57 mg/ | General | Local |
| | | Inhalation | m³ | population | |
| | DNEL | Short term | 640 mg/m ³ | General | Local |
| | | Inhalation | | population | |
| | DNEL | Long term | 837.5 mg/ | Workers | Local |
| | | Inhalation | m³ | | |
| | DNEL | Short term | 1066.67 | Workers | Local |
| | | Inhalation | mg/m³ | | |
| | DNEL | Short term | 1152 mg/ | General | Systemic |
| | | Inhalation | m³ | population | |
| | DNEL | Short term | 1286.4 mg/ | Workers | Systemic |
| | | Inhalation | m³ | | |
| Solvent naphtha (petroleum), heavy | DNEL | Long term Oral | 0.03 mg/ | General | Systemic |
| arom. | | | kg bw/day | population | |
| | DNEL | Long term Dermal | 0.28 mg/ | General | Systemic |
| | | | kg bw/day | population | |
| | DNEL | Long term | 0.69 mg/m ³ | General | Local |
| | | Inhalation | | population | |
| | DNEL | Long term | 0.69 mg/m ³ | | Systemic |
| | | Inhalation | | population | |
| | DNEL | Long term Dermal | 0.95 mg/ | Workers | Systemic |

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 8/23

▼ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 8: Exposure controls/personal protection

| | | | | kg bw/day | | |
|---|------------------------------------|-----------|-------------------|------------------------|------------|---------------|
| | | DNEL | Long term | 2.31 mg/m ³ | Workers | Local |
| | | | Inhalation | | | |
| | | DNEL | Long term | 2.31 mg/m ³ | Workers | Systemic |
| | | | Inhalation | · · | | |
| | | DNEL | Short term Oral | 25.6 mg/ | General | Systemic |
| | | | | kg bw/day | population | , |
| | | DNEL | Short term | 143.5 mg/ | General | Local |
| | | DIVLE | Inhalation | m ³ | population | Local |
| | | DNEL | Short term | 160.23 mg/ | Workers | Local |
| | | DIVLL | | m ³ | WOIKEIS | Local |
| | | DNEL | Inhalation | | Camaral | Customia |
| | | DNEL | Short term | 226 mg/m ³ | General | Systemic |
| | | - · · - · | Inhalation | 004 / 0 | population | |
| | | DNEL | Short term | 384 mg/m ³ | Workers | Systemic |
| | | | Inhalation | | | _ |
| | Solvent naphtha (petroleum), light | DNEL | Long term | 0.41 mg/m ³ | General | Systemic |
| | arom. | | Inhalation | | population | |
| | | DNEL | Long term | 1.9 mg/m³ | Workers | Systemic |
| | | | Inhalation | | | |
| | | DNEL | Long term | 178.57 mg/ | General | Local |
| | | | Inhalation | m³ | population | |
| | | DNEL | Short term | 640 mg/m ³ | General | Local |
| | | | Inhalation | 3 10 111 31 111 | population | |
| | | DNEL | Long term | 837.5 mg/ | Workers | Local |
| | | DIVLL | Inhalation | m³ | VVOIRCIS | Local |
| | | DNEL | Short term | 1066.67 | Workers | Local |
| | | DINEL | | | WOIKEIS | Local |
| | | חאורו | Inhalation | mg/m³ | 0 | C t : - |
| | | DNEL | Short term | 1152 mg/ | General | Systemic |
| | | | Inhalation | m³ | population | |
| | | DNEL | Short term | 1286.4 mg/ | Workers | Systemic |
| | | | Inhalation | m³ | | |
| | Reaction Mass of Ethylbenzene and | DNEL | Long term Oral | 1.6 mg/kg | General | Systemic |
| | M-Xylene and P-Xylene | | | bw/day | population | |
| | | DNEL | Long term | 14.8 mg/m ³ | General | Systemic |
| | | | Inhalation | | population | - |
| | | DNEL | Long term | 77 mg/m³ | Workers | Systemic |
| | | | Inhalation | J | | , |
| | | DNEL | Long term Dermal | 108 mg/kg | General | Systemic |
| | | D. 122 | Zong tonin Bonnar | bw/day | population | Cycleniic |
| | | DNEL | Long term Dermal | 180 mg/kg | Workers | Systemic |
| | | DIVLL | Long term berman | bw/day | VVOIRCIS | Cysternic |
| | | DNEL | Short term | 289 mg/m ³ | Workers | Local |
| | | DINEL | Inhalation | 209 mg/m | VVOIKEIS | Lucai |
| | | חארי | | 200 pa a / 3 | Morkoro | Customic |
| | | DNEL | Short term | 289 mg/m ³ | Workers | Systemic |
| | California mambilia - /tl | ראיבי | Inhalation | 0.44 / 2 | Camaral | Curata waii a |
| | Solvent naphtha (petroleum), light | DNEL | Long term | 0.41 mg/m ³ | General | Systemic |
| | arom. | - · · - · | Inhalation | | population | . |
| | | DNEL | Long term | 1.9 mg/m³ | Workers | Systemic |
| | | | Inhalation | | _ | |
| | | DNEL | Long term | 178.57 mg/ | General | Local |
| | | | Inhalation | m³ | population | |
| | | DNEL | Short term | 640 mg/m ³ | General | Local |
| | | | Inhalation | | population | |
| | | DNEL | Long term | 837.5 mg/ | Workers | Local |
| | | | Inhalation | m³ | | |
| | | DNEL | Short term | 1066.67 | Workers | Local |
| | | | Inhalation | mg/m³ | | |
| | | DNEL | Short term | 1152 mg/ | General | Systemic |
| | | | Inhalation | m ³ | population | - , 5.5.1110 |
| | | DNEL | Short term | 1286.4 mg/ | Workers | Systemic |
| | | J. 1LL | 2.10.1.101111 | 55. i iiig/ | | - , 5.5.1110 |
| ' | to of income/Data of maniping | | • | - | | |

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 9/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 8: Exposure controls/personal protection

| | | Inhalation | m³ | | |
|-------------------------------|-------------|-------------------------|------------------------|---|-----------|
| calcium bis(2-ethylhexanoate) | DNEL | Long term Oral | 0.167 mg/ | General | Systemic |
| | | 201.9 101111 01011 | kg bw/day | population | - , |
| | DNEL | Long term Dermal | 0.167 mg/ | General | Systemic |
| | DIVLL | Long tom Bonna | kg bw/day | population | Cyclonic |
| | DNEL | Long term Dermal | 0.333 mg/ | Workers | Systemic |
| | DIVLL | Long term Dermai | kg bw/day | WOIKCIS | Oysternio |
| | DNEL | Long term | 0.58 mg/m ³ | General | Systemic |
| | DINLL | Inhalation | 0.56 mg/m | population | Systernic |
| | DNEL | | 2 251 mg/ | Workers | Systemia |
| | DINEL | Long term Inhalation | 2.351 mg/ m³ | WOIKEIS | Systemic |
| needeennie geid, eehalt eelt | DNEL | | | General | Cuatamia |
| neodecanoic acid, cobalt salt | DNEL | Long term Oral | 32 µg/kg | | Systemic |
| | DAIEI | | bw/day | population | |
| | DNEL | Long term | 43 µg/m³ | General | Local |
| | | Inhalation | | population | |
| | DNEL | Long term | 273.2 μg/ | Workers | Local |
| | | Inhalation | m³ | | |
| Methyl ethyl ketoxime | DMEL | Long term Oral | 1.6 µg/kg | General | Systemic |
| | | | bw/day | population | |
| | DMEL | Long term Dermal | 4 µg/kg bw/ | Workers | Systemic |
| | | | day | | |
| | DMEL | Long term | 4.82 µg/m³ | General | Systemic |
| | | Inhalation | | population | |
| | DMEL | Long term | 28 µg/m³ | Workers | Systemic |
| | | Inhalation | | | |
| | DNEL | Long term | 0.43 mg/m ³ | General | Local |
| | | Inhalation | J | population | |
| | DNEL | Long term | 0.9 mg/m ³ | Workers | Local |
| | | Inhalation | J | | |
| Mesitylene | DNEL | Long term Oral | 15 mg/kg | General | Systemic |
| | | • | bw/day | population | , |
| | DNEL | Short term | 29.4 mg/m ³ | | Local |
| | | Inhalation | · | population | |
| | DNEL | Long term | 29.4 mg/m ³ | | Local |
| | J.,LL | Inhalation | _09/111 | population | |
| | DNEL | Short term | 29.4 mg/m ³ | | Systemic |
| | J.,LL | Inhalation | _09/111 | population | -,0.00 |
| | DNEL | Long term | 29.4 mg/m³ | | Systemic |
| | DI TLL | Inhalation | 20.4 mg/m | population | Cyclonic |
| | DNEL | Short term | 100 mg/m ³ | Workers | Local |
| | DITLL | Inhalation | 100 1119/111 | *************************************** | Looui |
| | DNEL | Long term | 100 mg/m ³ | Workers | Local |
| | DIVLL | Inhalation | 100 mg/m | VVOINGIS | Local |
| | DNEL | Short term | 100 mg/m³ | Workers | Systemic |
| | DIVLL | Inhalation | 100 mg/m | VVOIRCIS | Cystoniio |
| | DNEL | Long term | 100 mg/m ³ | Workers | Systemic |
| | DIVLL | Inhalation | 100 mg/m | VVOINGIS | Cysternic |
| | DNEL | Long term Dermal | 9512 mg/ | General | Systemic |
| | DINEL | Long term Dermal | | | Systemic |
| | סאובי | Long torm Daves | kg bw/day | population | Customic |
| | DNEL | Long term Dermal | 16171 mg/ | Workers | Systemic |
| | | | kg bw/day | | |

PNECs

No PNECs available.

8.2 Exposure controls

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 10/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 8: Exposure controls/personal protection

estimated.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 11/23

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Color : Various: See label.

Odor : Not available.
Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling : 138°C (280.4°F)

point, and boiling range

Flammability
Lower and upper explosion

limit

: Not available.

: Not available.

Flash point : Closed cup: 37°C (98.6°F) [Pensky-Martens]

Auto-ignition temperature

| Ingredient name | °C | °F | Method |
|---|------------|----------------|------------|
| Solvent naphtha (petroleum), heavy arom. | 220 to 250 | 428 to 482 | ASTM E 659 |
| Solvent naphtha (petroleum), heavy arom. | 220 to 250 | 428 to 482 | ASTM E 659 |
| 2-butoxyethanol | 230 | 446 | DIN 51794 |
| Solvent naphtha (petroleum) medium aliph | >220 | >428 | ASTM E 659 |
| Solvent naphtha (petroleum), medium aliph. | >220 | >428 | ASTM E 659 |
| Naphtha (petroleum), hydrodesulfurized heavy | 280 to 470 | 536 to 878 | |
| Solvent naphtha (petroleum), light arom. | 280 to 470 | 536 to 878 | |
| Solvent naphtha (petroleum), light arom. | 280 to 470 | 536 to 878 | |
| Naphtha (petroleum), hydrotreated heavy | 280 to 470 | 536 to 878 | |
| Methyl ethyl ketoxime | 314 to 317 | 597.2 to 602.6 | EU A.15 |
| Linseed oil | 342.85 | 649.1 | |
| pentan-2-ol | 342.85 | 649.1 | |
| butan-1-ol | 355 | 671 | EU A.15 |
| propane-1,2-diol | 371 | 699.8 | |
| stearic acid | 400 | 752 | |
| 2-methylpropan-1-ol | 415 | 779 | |
| Zinc stearate | 420 | 788 | |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | 432 | 809.6 | |
| Mesitylene | 559 | 1038.2 | |
| Phthalic anhydride | 580 | 1076 | _ |

Decomposition temperature: Not available.

pH : Not available. [DIN EN 1262]

Viscosity : Kinematic (room temperature): 67 mm²/s [DIN EN ISO 3219]

Kinematic (40°C): 67 mm²/s [DIN EN ISO 3219]

Solubility(ies) :

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 12/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 9: Physical and chemical properties

| Media | Result |
|------------|-----------------------------|
| cold water | Not soluble [OESO (TG 105)] |

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

| | Vapor Pressure at 20°C | | Va | Vapor pressure at 50°C | | |
|---|------------------------|------------|----------------|------------------------|-----|--------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| 2-methylpropan-1-ol | <12 | <1.6 | DIN EN 13016-2 | | | |
| butan-1-ol | <7.5 | <1 | DIN EN 13016-2 | | | |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | 6.7 | 0.89 | | | | |
| Mesitylene | 2.4 | 0.32 | | | | |
| Solvent naphtha (petroleum) medium aliph | 1.5 to 4.5 | 0.2 to 0.6 | | | | |
| Solvent naphtha (petroleum), medium aliph. | 1.5 to 4.5 | 0.2 to 0.6 | | | | |
| 2-butoxyethanol | 0.75 | 0.1 | | | | |
| Naphtha (petroleum), hydrotreated heavy | 0.75 to 2.25 | 0.1 to 0.3 | | | | |
| Solvent naphtha (petroleum), light arom. | 0.3 | 0.04 | | | | |
| Solvent naphtha (petroleum), light arom. | 0.3 | 0.04 | | | | |
| propane-1,2-diol | 0.15 | 0.02 | EU A.4 | | | |
| Solvent naphtha (petroleum), heavy arom. | 0.02 | 0.0027 | | | | |
| Solvent naphtha (petroleum), heavy arom. | 0.02 | 0.0027 | | | | |
| 2,6-di-tert-butyl-p-cresol | 0.01 | 0.0013 | | | | |
| Phthalic anhydride | 0.0022 | 0.00029 | | | | |
| Zinc stearate | 0 | 0 | | | | |

Relative density : 0.902

Density : 0.902 g/cm³ [DIN EN ISO 2811-1]

: 7-6-2023

Vapor density : Not available.

Particle characteristics

Date of issue/Date of revision

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

μm

Date of previous issue

:15-12-2022

Version :3

13/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 10: Stability and reactivity

10.1 Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

: The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

: Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-----------------------|---------|-------------|----------|
| Solvent naphtha (petroleum), medium aliph. | LC50 Inhalation Vapor | Rat | >5500 ppm | 4 hours |
| | LD50 Dermal | Rabbit | >3000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | LC50 Inhalation Gas. | Rat | 6670 ppm | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| Solvent naphtha (petroleum), light arom. | LD50 Oral | Rat | 8400 mg/kg | - |

Conclusion/Summary

: Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapors) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|---|------------------|-------------------|--------------------------------|----------------------------------|--|
| 8 826 | 52494.8 | 46084.7 | 279441.1 | N/A | N/A |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | 4300 | 1100 | 6670 | N/A | N/A |
| Solvent naphtha (petroleum), light arom. | 8400 | N/A | N/A | N/A | N/A |
| neodecanoic acid, cobalt salt | 500 | N/A | N/A | N/A | N/A |
| Methyl ethyl ketoxime | 100 | 1100 | N/A | N/A | N/A |

Irritation/Corrosion

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 14/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 11: Toxicological information

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|-------------------------|-------------|
| Solvent naphtha (petroleum), | Skin - Mild irritant | Rabbit | - | 24 hours 500 | - |
| heavy arom. Solvent naphtha (petroleum), | Eyes - Mild irritant | Rabbit | - | uL 24 hours 100 | - |
| light arom. Reaction Mass of | Eyes - Mild irritant | Rabbit | _ | uL 87 mg | _ |
| Ethylbenzene and M-Xylene and P-Xylene | Lyos Mila Ilmani | rassit | | or mg | |
| , | Eyes - Severe irritant | Rabbit | - | 24 hours 5 mg | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 UI | - |
| | Skin - Moderate irritant | Rabbit | - | 100 % | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 | - |
| | | | | mg | |
| Solvent naphtha (petroleum), light arom. | Eyes - Mild irritant | Rabbit | - | 24 hours 100 uL | - |
| Methyl ethyl ketoxime | Eyes - Severe irritant | Rabbit | - | 100 uL | - |
| Mesitylene | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | Skin - Moderate irritant | Rabbit | - | mg 24 hours 20 mg | - |

Conclusion/Summary

Sensitization

Conclusion/Summary

: Not available.

: Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|----------------------------|---------|---------|----------------------------|
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | Positive - Inhalation - TC | Mouse | <75 ppm | 103 weeks; 5 days per week |

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|------------------------------|
| Maphtha (petroleum), hydrodesulfurized heavy | Category 3 | - | Narcotic effects |
| Solvent naphtha (petroleum), heavy arom. | Category 3 | - | Respiratory tract irritation |
| Solvent naphtha (petroleum), light arom. | Category 3 | - | Respiratory tract irritation |
| | Category 3 | | Narcotic effects |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | Category 3 | - | Respiratory tract irritation |
| Solvent naphtha (petroleum), light arom. | Category 3 | - | Respiratory tract irritation |
| | Category 3 | | Narcotic effects |
| Methyl ethyl ketoxime | Category 1 | - | upper respiratory tract |
| | Category 3 | | Narcotic effects |

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 15/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 11: Toxicological information

| Mesitylene | Category 3 | - | Respiratory tract |
|------------|------------|---|-------------------|
| | | | irritation |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|---|------------|-------------------|---------------------------------|
| Maphtha (petroleum), hydrodesulfurized heavy | Category 2 | - | respiratory system |
| Solvent naphtha (petroleum), medium aliph. | Category 1 | - | central nervous system (CNS) |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | Category 2 | - | - |
| Methyl ethyl ketoxime | Category 2 | - | blood system |

Aspiration hazard

| Product/ingredient name | Result |
|---|--------------------------------|
| Naphtha (petroleum), hydrodesulfurized heavy | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum) medium aliph | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), medium aliph. | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), heavy arom. | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), light arom. | ASPIRATION HAZARD - Category 1 |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | ASPIRATION HAZARD - Category 1 |
| Solvent naphtha (petroleum), light arom. | ASPIRATION HAZARD - Category 1 |

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact: No known significant effects or critical hazards.

Ingestion: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation: Adverse symptoms may include the following:

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

<u>Delayed and immediate effects and also chronic effects from short and long term exposure</u> Short term exposure

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 16/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 11: Toxicological information

Potential immediate

effects

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.

Reproductive toxicity: May damage the unborn child.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name | Result | Species | Exposure |
|---|--|--|---------------------|
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | Acute LC50 8.5 ppm Marine water | Crustaceans - Palaemonetes pugio - Adult | 48 hours |
| | Acute LC50 8500 μg/l Marine water | Crustaceans - Palaemonetes pugio | 48 hours |
| | Acute LC50 15700 μg/l Fresh water | Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| Mesitylene | Acute LC50 13400 µg/l Fresh water Chronic NOEC 0.4 mg/l Fresh water | Fish - Pimephales promelas Daphnia - Daphnia magna | 96 hours 21 days |

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | - | - | Readily |

12.3 Bioaccumulative potential

| Date of issue/Date of revision | : 7-6-2023 | Date of previous issue | : 15-12-2022 | Version : 3 | 17/23 |
|--------------------------------|------------|------------------------|--------------|-------------|-------|
|--------------------------------|------------|------------------------|--------------|-------------|-------|

₹ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 12: Ecological information

| Product/ingredient name | LogPow | BCF | Potential |
|---|------------|-------------|-----------|
| Maphtha (petroleum), hydrodesulfurized heavy | - | 10 to 2500 | high |
| Solvent naphtha (petroleum), heavy arom. | 2.8 to 6.5 | 99 to 5780 | high |
| Solvent naphtha (petroleum), light arom. | - | 10 to 2500 | high |
| Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene | 3.12 | 8.1 to 25.9 | low |
| Solvent naphtha (petroleum), light arom. | - | 10 to 2500 | high |
| calcium bis (2-ethylhexanoate) | - | 2.96 | low |
| neodecanoic acid, cobalt salt | - | 15600 | high |
| Methyl ethyl ketoxime | 0.63 | 2.5 to 5.8 | low |
| Mesitylene | 3.42 | 161 | low |

12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 18/23

▼ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 13: Disposal considerations

| Waste code | Waste designation |
|---------------|---|
| EWC 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | IMDG |
|----------------------------------|---------|---|
| 14.1 UN number | UN1263 | UN1263 |
| 14.2 UN proper shipping name | PAINT | PAINT |
| 14.3 Transport hazard class(es) | 3 | 3 |
| 14.4 Packing group | III | III |
| 14.5 Environmental hazards | Yes. | Marine Pollutant(s): Naphtha (petroleum), hydrodesulfurized heavy, Solvent naphtha (petroleum), heavy arom. |

Additional information

ADR/RID

: The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Tunnel code (D/E)

IMDG

: Emergency schedules F-E, S-E

The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

14.6 Special precautions for

user

: **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 19/23

₹ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Restricted to professional users. on the manufacture, placing on the market

and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: Not available.

Industrial emissions (integrated pollution

(integrated pollution prevention and control) -

: Not listed

: Not listed

Air

Industrial emissions (integrated pollution

prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

E2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 20/23

₹ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 15: Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-------------------------|-----------------------|
| Fam. Liq. 3, H226 | On basis of test data |
| Carc. 1B, H350 | Calculation method |
| Repr. 1B, H360D | Calculation method |
| STOT SE 3, H336 | Calculation method |
| STOT RE 2, H373 | Calculation method |
| Aquatic Chronic 2, H411 | Calculation method |

Full text of abbreviated H statements

| ⊮ 226 | Flammable liquid and vapor. |
|--------------|--|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H350 | May cause cancer. |
| H360D | May damage the unborn child. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H370 | Causes damage to organs. |
| H372 | Causes damage to organs through prolonged or repeated |
| | exposure. |
| H373 | May cause damage to organs through prolonged or repeated |
| | exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Date of previous issue Version : 3 21/23

▼ WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

SECTION 16: Other information

Full text of classifications [CLP/GHS]

Acute Tox. 3 **ACUTE TOXICITY - Category 3** Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3 Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Carc. 1B **CARCINOGENICITY - Category 1B** Eve Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Eye Irrit. 2 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Repr. 1B TOXIC TO REPRODUCTION - Category 1B Repr. 2 **TOXIC TO REPRODUCTION - Category 2** Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITIZATION - Category 1 STOT RE 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

STOT SE 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 1

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

Date of printing Date of issue/ Date of

revision

: 23-6-2023 : 7-6-2023

Date of previous issue : 15-12-2022

: 3 Version

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 22/23

WOODGARD EXT TIMBAPRESERVATIVE SB MAHOGANY

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 3 23/23