AkzoNobel



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET

WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

GHS product identifier : ▼WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product use : Use in accordance with directions on the can.

1.3. Details of the supplier of the safety data sheet

ICI DULUX (PTY) LTD NO. 1 PAINTS PLACE DICKENS ROAD UMBOGINTWINI

4126

SOUTH AFRICA

e-mail address of person responsible for this SDS

: ZA.Helpline@akzonobel.com

1.4 Emergency telephone number

Supplier

Telephone number: Customer Care 0860 330 111 (Available week days from 08:00 to 16:30)

Emergency details: after hours: refer to website for MSDS

Version : 4

Date of previous issue : 15-12-2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Fam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360D STOT RE 2, H373 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 2: Hazards identification

Hazard pictograms







Signal word : Danger

Hazard statements : F226 - Flammable liquid and vapor.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H360D - May damage the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General : P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention : P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing, eye protection, face protection,

or hearing protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P273 - Avoid release to the environment.

P260 - Do not breathe vapor.

P264 - Wash hands thoroughly after handling.

: P308 + P313 - IF exposed or concerned: Get medical advice or attention. Response

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

: P405 - Store locked up. Storage

P403 + P235 - Store in a well-ventilated place. Keep cool.

: P501 - Dispose of contents and container in accordance with all local, regional, Disposal

national or international regulations.

: Naphtha (petroleum), hydrodesulfurized heavy Hazardous ingredients

Hydrocarbons, terpene processing by-products

calcium bis(2-ethylhexanoate) neodecanoic acid, cobalt salt

Supplemental label

elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

substances, mixtures and

articles

: Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant

: Yes, applicable.

fastenings

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a

vPvB.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version: 4 2/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 2: Hazards identification

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Solvent naphtha (petroleum), medium aliph.	EC: 265-191-7 CAS: 64742-88-7	≥25 - ≤49	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/	[1]
Naphtha (petroleum), hydrodesulfurized heavy	EC: 265-185-4 CAS: 64742-82-1	≥10 - ≤15	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 2, H373 (respiratory system) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
Reaction Mass of Ethylbenzene and M- Xylene and P-Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≤3	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 6670 ppm	[1] [2]
Hydrocarbons, terpene processing by-products	EC: 273-309-3 CAS: 68956-56-9	≤2.9	Flam. Liq. 3, H226 Skin Corr. 1, H314 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	-	[1]
Solvent naphtha (petroleum), heavy arom.	EC: 265-198-5 CAS: 64742-94-5	≤2	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ I	[1]
calcium bis (2-ethylhexanoate)	REACH #: 01-2119978297-19 EC: 205-249-0 CAS: 136-51-6	<1	Eye Dam. 1, H318 Repr. 1B, H360D	-	[1]
neodecanoic acid, cobalt salt	EC: 248-373-0 CAS: 27253-31-2	<1	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 3/20

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 4/20

${f 7}$ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 4: First aid measures

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains Hydrocarbons, terpene processing by-products, neodecanoic acid, cobalt salt. May produce an allergic reaction.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and

prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 5/20

✓ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical

: 7-6-2023 Date of previous issue : 15-12-2022 Version: 4 Date of issue/Date of revision 6/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 7: Handling and storage

Advice on general occupational hygiene

(ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8.2 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold	
P5c	5000 tonne	50000 tonne	

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 7/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 8: Exposure controls/personal protection

required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Naphtha (petroleum),	DNEL	Long term	0.41 mg/m ³	General	Systemic
hydrodesulfurized heavy	DNE	Inhalation	4.0/3	population	0
	DNEL	Long term Inhalation	1.9 mg/m³	Workers	Systemic
	DNEL	Long term	178.57 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Short term	640 mg/m ³	General	Local
	DNEL	Inhalation Long term	927 5 mg/	population Workers	Local
	DINEL	Inhalation	837.5 mg/ m³	VVOIKEIS	Local
	DNEL	Short term	1066.67	Workers	Local
		Inhalation	mg/m³		
	DNEL	Short term	1152 mg/	General	Systemic
	DNEL	Inhalation Short term	m ³	population Workers	Systemia
	DINEL	Inhalation	1286.4 mg/ m³	vvoikeis	Systemic
Reaction Mass of Ethylbenzene and	DNEL	Long term Oral	1.6 mg/kg	General	Systemic
M-Xylene and P-Xylene			bw/day	population	,
	DNEL	Long term	14.8 mg/m³	General	Systemic
	DNE	Inhalation	77 / 3	population	0
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	108 mg/kg	General	Systemic
			bw/day	population	,
	DNEL	Long term Dermal	180 mg/kg	Workers	Systemic
	DNE	Ch aut tauma	bw/day	\\/awlsawa	Lacel
	DNEL	Short term Inhalation	289 mg/m ³	Workers	Local
	DNEL	Short term	289 mg/m ³	Workers	Systemic
		Inhalation	J		
Hydrocarbons, terpene processing	DNEL	Long term Oral	0.3 mg/kg	General	Systemic
by-products	DNEL	Long term Dermal	bw/day	population General	Systemic
	DINEL	Long term Dermai	0.3 mg/kg bw/day	population	Systemic
	DNEL	Long term	0.7 mg/m ³	General	Systemic
		Inhalation		population	-
	DNEL	Long term Dermal	0.8 mg/kg	Workers	Systemic
	DNEL	Long term	bw/day 2.9 mg/m³	Workers	Systemic
	DINCL	Inhalation	2.9 mg/m	VVOIKEIS	Systemic
Solvent naphtha (petroleum), heavy	DNEL	Long term Oral	0.03 mg/	General	Systemic
arom.			kg bw/day	population	
	DNEL	Long term Dermal	0.28 mg/	General	Systemic
	DNEL	Long term	kg bw/day 0.69 mg/m³	population General	Local
	DIVLE	Inhalation	0.00 mg/m	population	Local
	DNEL	Long term	0.69 mg/m ³		Systemic
		Inhalation		population	
	DNEL	Long term Dermal	0.95 mg/	Workers	Systemic
	DNEL	Long term	kg bw/day 2.31 mg/m³	Workers	Local
		Inhalation			
	DNEL	Long term	2.31 mg/m ³	Workers	Systemic
	D	Inhalation	05.0. /	0	01
	DNEL	Short term Oral	25.6 mg/ kg bw/day	General population	Systemic
			Ng Dw/day	population	

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 8/20

₹ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 8: Exposure controls/personal protection

	DNEL	Short term	143.5 mg/	General	Local
		Inhalation	m³	population	
	DNEL	Short term	160.23 mg/		Local
		Inhalation	m³		
	DNEL	Short term	226 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Short term	384 mg/m ³	Workers	Systemic
		Inhalation			
calcium bis(2-ethylhexanoate)	DNEL	Long term Oral	0.167 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.167 mg/	General	Systemic
	DAIE	D	kg bw/day	population	0
	DNEL	Long term Dermal	0.333 mg/	Workers	Systemic
	DNEL	Long torm	kg bw/day	General	Systemic
	DINEL	Long term Inhalation	0.58 mg/m ³	population	Systemic
	DNEL	Long term	2.351 mg/	Workers	Systemic
	DIVLL	Inhalation	m ³	WOIKEIS	Systernic
neodecanoic acid, cobalt salt	DNEL	Long term Oral	32 µg/kg	General	Systemic
noodocanolo dold, cobalt calt		Long tom oran	bw/day	population	Cyclonic
	DNEL	Long term	43 µg/m³	General	Local
		Inhalation	1 3	population	
	DNEL	Long term	273.2 μg/	Workers	Local
		Inhalation	m³		
<u> </u>			l .		

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 9/20

WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 8: Exposure controls/personal protection

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton @ or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personal protective equipment for the body should be selected based on the task

being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design

requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Color : Various: See label.

Odor : Not available.

Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling point, and boiling range

Flammability : Not available.

Lower and upper explosion : Not available.

limit

_. .

Flash point : Closed cup: 35°C (95°F) [Pensky-Martens]

Auto-ignition temperature :

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 10/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
Solvent naphtha (petroleum), heavy arom.	220 to 250	428 to 482	ASTM E 659
Solvent naphtha (petroleum), heavy arom.	220 to 250	428 to 482	ASTM E 659
Solvent naphtha (petroleum), heavy arom.	220 to 250	428 to 482	ASTM E 659
2-butoxyethanol	230	446	DIN 51794
Solvent naphtha (petroleum), medium aliph.	>220	>428	ASTM E 659
Naphtha (petroleum), hydrodesulfurized heavy	280 to 470	536 to 878	
Methyl ethyl ketoxime	314 to 317	597.2 to 602.6	EU A.15
pentan-2-ol	342.85	649.1	
butan-1-ol	355	671	EU A.15
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	432	809.6	
Mesitylene	559	1038.2	
Phthalic anhydride	580	1076	

Decomposition temperature: Not available.

pH : Not available. [DIN EN 1262]

Viscosity : Kinematic: 257 mm²/s [DIN EN ISO 3219]

Solubility(ies) :

Media	Result
cold water	Not soluble [OESO (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure :

	Vapor Pressure at 20°C			V	sure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
butan-1-ol	<7.5	<1	DIN EN 13016-2			
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	6.7	0.89				
Mesitylene	2.4	0.32				
Solvent naphtha (petroleum), medium aliph.	1.5 to 4.5	0.2 to 0.6				
2-butoxyethanol	0.75	0.1				
Solvent naphtha (petroleum), heavy arom.	0.02	0.0027				
Solvent naphtha (petroleum), heavy arom.	0.02	0.0027				
Solvent naphtha (petroleum), heavy arom.	0.02	0.0027				
2,6-di-tert-butyl-p-cresol	0.01	0.0013				
Phthalic anhydride	0.0022	0.00029				

Relative density : 0.9

Density : 0.9 g/cm³ [DIN EN ISO 2811-1]

Vapor density : Not available.

Particle characteristics

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 11/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 9: Physical and chemical properties

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

μm

: 0

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	LC50 Inhalation Gas.	Rat	6670 ppm	4 hours
Solvent naphtha	LD50 Oral LD50 Oral LDLo Oral	Rat Rat Rat	4300 mg/kg 4300 mg/kg 5 mL/kg	- - -
(petroleum), heavy arom.				

Conclusion/Summary: Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
88832	N/A	3344.9	291517	36	N/A
Solvent naphtha (petroleum), medium aliph.	N/A	1100	N/A	11	N/A
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	4300	1100	6670	N/A	N/A
Solvent naphtha (petroleum), heavy arom. neodecanoic acid, cobalt salt	N/A 500	1100 N/A	N/A N/A	11 N/A	N/A N/A

Irritation/Corrosion

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 12/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
·	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Solvent naphtha (petroleum), heavy arom.	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-

Conclusion/Summary

: Not available.

Sensitization

Conclusion/Summary

: Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	Positive - Inhalation - TC	Mouse	<75 ppm	103 weeks; 5 days per week

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary : N

: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy Reaction Mass of Ethylbenzene and M-Xylene and P-	Category 3 Category 3	-	Narcotic effects Respiratory tract
Xylene	Category 5	-	irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy Reaction Mass of Ethylbenzene and M-Xylene and P- Xylene	Category 2 Category 2	-	respiratory system -

Aspiration hazard

Product/ingredient name	Result
Solvent naphtha (petroleum), medium aliph.	ASPIRATION HAZARD - Category 1
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	ASPIRATION HAZARD - Category 1
Hydrocarbons, terpene processing by-products	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), heavy arom.	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Not available.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 13/20

₹ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 11: Toxicological information

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very

low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity: May damage the unborn child.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 14/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	Acute LC50 8.5 ppm Marine water	Crustaceans - Palaemonetes pugio - Adult	48 hours
,	Acute LC50 8500 μg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 15700 μg/l Fresh water	Fish - Lepomis macrochirus - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 13400 μg/l Fresh water	Fish - Pimephales promelas	96 hours

Conclusion/Summary: Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Reaction Mass of Ethylbenzene and M-Xylene and P-Xylene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Maphtha (petroleum), hydrodesulfurized heavy	-	10 to 2500	high
Reaction Mass of Ethylbenzene and M-Xylene	3.12	8.1 to 25.9	low
and P-Xylene Solvent naphtha (petroleum), heavy arom.	2.8 to 6.5	99 to 5780	high
calcium bis (2-ethylhexanoate)	-	2.96	low
neodecanoic acid, cobalt salt	-	15600	high

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility

: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 15/20

▼WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 12: Ecological information

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT
14.3 Transport hazard class(es)	3	3
14.4 Packing group	III	III

✓ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 14: Transport information

14.5 No. **Environmental** hazards

Additional information

ADR/RID : Tunnel code (D/E)

IMDG : Emergency schedules F-E, S-E

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO

instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Annex XVII - Restrictions: Restricted to professional users.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: Not available.

Industrial emissions (integrated pollution prevention and control) - : Not listed

Air

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Date of issue/Date of revision : 7-6-2023 : 15-12-2022 Version: 4 17/20 Date of previous issue

₹ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 15: Regulatory information

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

Assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Mam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360D	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 18/20

₹ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 16: Other information

Flammable liquid and vapor. H302 H304 H312 H314 H315 H315 H317 Flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction.	
H304 H312 H314 H314 H315 May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation.	
H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation.	
H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation.	
H315 Causes skin irritation.	
H317 May cause an allergic skin reaction.	
H318 Causes serious eye damage.	
H319 Causes serious eye irritation.	
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H360D May damage the unborn child.	
H361 Suspected of damaging fertility or the unborn chi	ild.
H373 May cause damage to organs through prolonged	d or repeated
exposure.	·
H411 Toxic to aquatic life with long lasting effects.	
H412 Harmful to aquatic life with long lasting effects.	

Full text of classifications [CLP/GHS]

Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3 Asp. Tox. 1 ASPIRATION HAZARD - Category 1 Eve Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 Eve Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Repr. 1B TOXIC TO REPRODUCTION - Category 1B Repr. 2 TOXIC TO REPRODUCTION - Category 2 Skin Corr. 1 SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2 Skin Sens. 1 SKIN SENSITIZATION - Category 1 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -Category 3

Date of printing : 23-6-2023 Date of issue/ Date of : 7-6-2023

Date of issue/ Date of revision

Date of previous issue

: 15-12-2022

Version : 4

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Safety Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 19/20

▼ WOODGARD INT/EXT TIMBAVARNISH SB MAHOGANY

SECTION 16: Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands

Date of issue/Date of revision : 7-6-2023 Date of previous issue : 15-12-2022 Version : 4 20/20